

### COMPRESSOR DEFINITION

Designation	<b>NE 9213GK</b>
Nominal Voltage/Frequency	<b>208-230 V 60 Hz</b>
Engineering Number	<b>953ED71</b>

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	208-230 / 60	[ V / Hz ]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 0°C	(-4°F to 32°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	25.7	[kgf/cm <sup>2</sup> ] (365 psig)	/ °C - °F
9.2 Peak (gauge)	28.7	[kgf/cm <sup>2</sup> ] (408 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	12.11	[cm <sup>3</sup> ] (0.739 cu.in)
2.1 Bore [mm]	27.775	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.6	[kg] (25.57 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	208-230 V 60 Hz 1~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA2AM3C-104	
3 Start capacitor	88-108(330)	[µF(VAC minimum)]
4 Run capacitor	15(450)	[µF(VAC minimum)]
5 Motor protection	T0188/G9	
6 Start winding resistance	11.30	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	3.13	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	24.80	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	4.90	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

### D - PERFORMANCE - CHECK POINT DATA

### E - PERFORMANCE - CURVES

TEST CONDITIONS:		ASHRAE46			(Condensing temperature 35°C (+95°F) )					
@200V60Hz		Fan								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-20 (- 4)	3088	778	905	540	2.70	19.60	5.72	1.44	1.68	
-15 (+ 5)	3945	994	1156	603	2.94	25.18	6.54	1.65	1.92	
-10 (+14)	4943	1246	1448	668	3.22	31.75	7.40	1.86	2.17	
-5 (+23)	6081	1532	1782	735	3.53	39.35	8.28	2.09	2.42	
0 (+32)	7359	1854	2156	804	3.87	48.03	9.15	2.31	2.68	
+5 (+41)	8776	2212	2572	875	4.23	57.85	10.01	2.52	2.93	
+10 (+50)	10332	2604	3028	948	4.60	68.85	10.84	2.73	3.18	

TEST CONDITIONS:		ASHRAE46			(Condensing temperature 45°C (+113°F) )					
@200V60Hz		Fan								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-20 (- 4)	2613	658	766	543	2.68	18.31	4.81	1.21	1.41	
-15 (+ 5)	3344	843	980	613	2.99	23.56	5.46	1.37	1.60	
-10 (+14)	4209	1061	1233	686	3.32	29.86	6.13	1.55	1.80	
-5 (+23)	5208	1312	1526	763	3.69	37.26	6.83	1.72	2.00	
0 (+32)	6340	1598	1858	843	4.07	45.81	7.52	1.90	2.20	
+5 (+41)	7605	1916	2228	927	4.47	55.55	8.20	2.07	2.40	
+10 (+50)	9002	2268	2638	1014	4.88	66.55	8.85	2.23	2.59	

TEST CONDITIONS:		ASHRAE46			(Condensing temperature 55°C (+131°F) )					
@200V60Hz		Fan								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-20 (- 4)	2119	534	621	547	2.66	16.66	3.87	0.98	1.13	
-15 (+ 5)	2718	685	796	623	3.03	21.52	4.36	1.10	1.28	
-10 (+14)	3444	868	1009	705	3.43	27.48	4.89	1.23	1.43	
-5 (+23)	4298	1083	1259	791	3.84	34.62	5.43	1.37	1.59	
0 (+32)	5278	1330	1547	883	4.27	42.96	5.98	1.51	1.75	
+5 (+41)	6384	1609	1871	980	4.71	52.57	6.51	1.64	1.91	
+10 (+50)	7616	1919	2232	1081	5.16	63.50	7.01	1.77	2.05	

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.03 +0.07/+0.00	[mm]	(0.316" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		