

### COMPRESSOR DEFINITION

Designation	<b>NE 7210E</b>
Nominal Voltage/Frequency	<b>115 V 60 Hz</b>
Engineering Number	<b>262TG71</b>

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-22		
3 Nominal voltage and frequency	115 / 60	[ V / Hz ]	
4 Application type	Air Conditioning		
4.1 Evaporating temperature range	0°C to 15°C	(32°F to 59°F)	
5 Motor type	PSC		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	21.7	[kgf/cm <sup>2</sup> ] (309 psig)	/ °C - °F
9.2 Peak (gauge)	24.2	[kgf/cm <sup>2</sup> ] (344 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/2-	[hp]
2 Displacement	8.77	[cm <sup>3</sup> ] (0.535 cu.in)
2.1 Bore [mm]	26.497	
2.2 Stroke [mm]	15.920	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	MINERAL / ISO32	
4 Weight (with oil charge)	10.65	[kg] (23.48 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1~ (Single phase)	
2 Starting device type	PSC	
2.1 Starting device		
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	15(450)	[µF(VAC minimum)]
5 Motor protection	T0558/G9	
6 Start winding resistance	10.55	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.36	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	28.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	6.00	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
4992	1258	1463	598	5.40	30.83	8.35	2.10	2.45

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V50Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0 (+32)	3554	896	1042	373	3.40	18.81	9.51	2.40	2.79
+5 (+41)	4234	1067	1241	392	3.57	22.86	10.82	2.73	3.17
+10 (+50)	5075	1279	1487	411	3.74	27.49	12.35	3.11	3.62
+15 (+59)	6078	1532	1781	432	3.90	- 0.05	14.06	3.54	4.12

TEST CONDITIONS: @115V50Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0 (+32)	3289	829	964	410	3.73	18.91	8.03	2.02	2.35
+5 (+41)	4045	1019	1185	439	3.96	23.12	9.21	2.32	2.70
+10 (+50)	4871	1228	1427	464	4.19	27.79	10.50	2.65	3.08
+15 (+59)	5766	1453	1690	486	4.40	0.18	11.86	2.99	3.48

TEST CONDITIONS: @115V50Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0 (+32)	3160	796	926	447	4.03	19.33	7.06	1.78	2.07
+5 (+41)	3798	957	1113	483	4.32	23.41	7.85	1.98	2.30
+10 (+50)	4415	1112	1294	511	4.59	27.84	8.66	2.18	2.54
+15 (+59)	5007	1262	1467	531	4.82	- 0.13	9.42	2.37	2.76

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0 (+32)	4269	1076	1251	450	4.10	22.70	9.48	2.39	2.78
+5 (+41)	5123	1291	1501	473	4.31	27.51	10.84	2.73	3.18
+10 (+50)	6122	1543	1794	496	4.51	33.14	12.35	3.11	3.62
+15 (+59)	7318	1844	2144	521	4.70	- 0.02	14.04	3.54	4.11

### E - PERFORMANCE - CURVES

TEST CONDITIONS:		ASHRAE46			(Condensing temperature 45°C (+113°F))					
@115V60Hz		Fan								
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0	(+32)	3983	1004	1167	494	4.50	22.76	8.06	2.03	2.36
+5	(+41)	4852	1223	1422	529	4.78	27.80	9.17	2.31	2.69
+10	(+50)	5813	1465	1703	559	5.05	33.45	10.40	2.62	3.05
+15	(+59)	6916	1743	2026	586	5.30	0.11	11.80	2.97	3.46

TEST CONDITIONS:		ASHRAE46			(Condensing temperature 55°C (+131°F))					
@115V60Hz		Fan								
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0	(+32)	3801	958	1114	539	4.86	23.29	7.05	1.78	2.06
+5	(+41)	4576	1153	1341	583	5.21	28.29	7.85	1.98	2.30
+10	(+50)	5389	1358	1579	616	5.53	33.71	8.76	2.21	2.57
+15	(+59)	6290	1585	1843	640	5.81	- 0.08	9.82	2.47	2.88

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.03 +0.07/+0.00	[mm]	(0.316" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		