

COMPRESSOR DEFINITION

Designation	NJ 6226Z
Nominal Voltage/Frequency	208-230 V 60 Hz
Engineering Number	142HD04

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	208-230 / 60	[V / Hz]	
4 Application type	High Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1 1/4	[hp]
2 Displacement	34.38	[cm ³] (2.098 cu.in)
2.1 Bore [mm]	42.850	
2.2 Stroke [mm]	23.850	
3 Lubricant charge	750	[ml] (25.36 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	19.85	[kg] (43.76 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	208-230 V 60 Hz 1~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA4M3C-109	
3 Start capacitor	72-88(330)	[µF(VAC minimum)]
4 Run capacitor	17.5(440)	[µF(VAC minimum)]
5 Motor protection	T0820/20	
6 Start winding resistance	8.47	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.51	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	40.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @208V60Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
11130	2805	3261	1445	7.23	72.16	7.70	1.94	2.26

E - PERFORMANCE - CURVES

TEST CONDITIONS: @208V60Hz		ASHRAE46 Fan				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	5508	1388	1614	783	3.97	29.76	7.05	1.78	2.07
-10	(+14)	7180	1809	2104	886	4.44	38.97	8.11	2.04	2.38
-5	(+23)	9075	2287	2659	992	4.94	49.45	9.15	2.30	2.68
0	(+32)	11193	2821	3280	1100	5.45	61.26	10.17	2.56	2.98
+5	(+41)	13534	3411	3966	1209	5.98	74.46	11.19	2.82	3.28
+10	(+50)	16099	4057	4717	1317	6.54	89.10	12.21	3.08	3.58

TEST CONDITIONS: @208V60Hz		ASHRAE46 Fan				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	4552	1147	1334	776	3.94	26.62	5.85	1.47	1.71
-10	(+14)	6021	1517	1764	897	4.51	35.31	6.70	1.69	1.96
-5	(+23)	7716	1944	2261	1026	5.11	45.41	7.52	1.89	2.20
0	(+32)	9636	2428	2824	1161	5.76	57.00	8.31	2.09	2.43
+5	(+41)	11782	2969	3452	1300	6.44	70.12	9.07	2.29	2.66
+10	(+50)	14154	3567	4147	1442	7.16	84.83	9.83	2.48	2.88

TEST CONDITIONS: @208V60Hz		ASHRAE46 Fan				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	3442	867	1008	767	3.90	21.94	4.50	1.13	1.32
-10	(+14)	4777	1204	1400	904	4.54	30.54	5.29	1.33	1.55
-5	(+23)	6340	1598	1858	1053	5.25	40.71	6.02	1.52	1.76
0	(+32)	8131	2049	2383	1211	6.01	52.51	6.71	1.69	1.97
+5	(+41)	10151	2558	2974	1378	6.84	65.99	7.36	1.85	2.16
+10	(+50)	12399	3124	3633	1552	7.73	81.22	7.98	2.01	2.34

F - EXTERNAL CHARACTERISTICS

1 Base plate	American Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	8 +0.07/+0.00	[mm]	(0.315" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted J		
3.3 PROCESS	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		