

COMPRESSOR DEFINITION

Designation	EM 50HNP
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513302851

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	187 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	187 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/8	[hp]
2 Displacement	4.99	[cm ³] (0.305 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	14.400	
3 Lubricant charge	160	[ml] (5.41 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	7.6	[kg] (16.75 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA17C3/8EA5B3/QPS2-A22MD3	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	2(330)	[µF(VAC minimum)]
5 Motor protection	4TM189RHBYY-53	
6 Start winding resistance	24.50	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	17.90	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - CE - IRAM - UKCA - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
425	107	125	106	0.82	2.41	4.02	1.01	1.18

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	178	45	52	73	0.73	1.00	2.46	0.62	0.72
-30 (-22)	288	73	84	87	0.79	1.63	3.30	0.83	0.97
-25 (-13)	409	103	120	99	0.81	2.32	4.13	1.04	1.21
-20 (- 4)	547	138	160	110	0.82	3.11	4.95	1.25	1.45
-15 (+ 5)	711	179	208	122	0.83	4.06	5.80	1.46	1.70
-10 (+14)	907	228	266	135	0.86	5.20	6.67	1.68	1.96

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	150	38	44	72	0.76	0.85	2.09	0.53	0.61
-30 (-22)	252	63	74	87	0.78	1.43	2.87	0.72	0.84
-25 (-13)	365	92	107	101	0.79	2.07	3.62	0.91	1.06
-20 (- 4)	499	126	146	115	0.81	2.84	4.36	1.10	1.28
-15 (+ 5)	661	167	194	129	0.87	3.77	5.11	1.29	1.50
-10 (+14)	858	216	251	145	0.97	4.91	5.88	1.48	1.72

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	109	27	32	65	0.73	0.62	1.66	0.42	0.49
-30 (-22)	197	50	58	82	0.72	1.12	2.40	0.60	0.70
-25 (-13)	300	76	88	98	0.74	1.70	3.10	0.78	0.91
-20 (- 4)	426	107	125	114	0.79	2.42	3.77	0.95	1.11
-15 (+ 5)	581	147	170	131	0.90	3.32	4.45	1.12	1.30
-10 (+14)	775	195	227	150	1.09	4.44	5.14	1.30	1.51

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		