

COMPRESSOR DEFINITION

Designation	EM Y26CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	894HA73

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low-Medium Back Pressure		
4.1 Evaporating temperature range	-35°C to -5°C	(-31°F to 23°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	Static	187 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	7.7	[kgf/cm ²] (109 psig)	/ °C - °F
9.2 Peak (gauge)	9.8	[kgf/cm ²] (139 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	5.19	[cm ³] (0.317 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	MINERAL / ISO7	
4 Weight (with oil charge)	7.7	[kg] (16.98 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	MSDA3	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	2.5(450)	[µF(VAC minimum)]
5 Motor protection	4TM110NFBYY-153	
6 Start winding resistance	28.50	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	43.20	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	2.25	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.70	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
290	73	85	57	0.25	0.91	5.09	1.28	1.49

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	148	37	43	40	0.19	0.46	3.69	0.93	1.08
-30 (-22)	210	53	61	47	0.21	0.66	4.49	1.13	1.32
-25 (-13)	283	71	83	53	0.24	0.89	5.32	1.34	1.56
-20 (- 4)	368	93	108	60	0.27	1.16	6.18	1.56	1.81
-15 (+ 5)	468	118	137	66	0.29	1.47	7.07	1.78	2.07
-10 (+14)	583	147	171	73	0.32	1.84	7.99	2.01	2.34
-5 (+23)	715	180	209	80	0.35	2.26	8.94	2.25	2.62

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	135	34	40	41	0.19	0.42	3.29	0.83	0.96
-30 (-22)	193	49	56	48	0.21	0.60	4.04	1.02	1.18
-25 (-13)	262	66	77	55	0.24	0.82	4.79	1.21	1.40
-20 (- 4)	346	87	101	62	0.27	1.09	5.54	1.40	1.62
-15 (+ 5)	443	112	130	70	0.31	1.40	6.29	1.58	1.84
-10 (+14)	557	140	163	79	0.34	1.76	7.04	1.77	2.06
-5 (+23)	687	173	201	88	0.38	2.17	7.80	1.96	2.28

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	119	30	35	41	0.19	0.37	2.92	0.74	0.85
-30 (-22)	173	44	51	48	0.21	0.54	3.63	0.92	1.06
-25 (-13)	240	60	70	56	0.24	0.75	4.32	1.09	1.27
-20 (- 4)	320	81	94	64	0.28	1.01	4.98	1.25	1.46
-15 (+ 5)	416	105	122	74	0.32	1.31	5.61	1.41	1.64
-10 (+14)	528	133	155	85	0.37	1.67	6.21	1.56	1.82
-5 (+23)	657	166	193	97	0.42	2.08	6.78	1.71	1.99

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.95 +0.05/+0.05	[mm]	(0.195" +0.002"/+0.002")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		