

COMPRESSOR DEFINITION

Designation	EM T32CLP
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	891CA78

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low-Medium Back Pressure		
4.1 Evaporating temperature range	-35°C to -5°C	(-31°F to 23°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	7.7	[kgf/cm ²] (109 psig)	/ °C - °F
9.2 Peak (gauge)	9.8	[kgf/cm ²] (139 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	5.96	[cm ³] (0.364 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	MINERAL / ISO7	
4 Weight (with oil charge)	7.3	[kg] (16.09 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	2019	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	2.5(450)	[µF(VAC minimum)]
5 Motor protection	AD37FN10	
6 Start winding resistance	32.00	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	31.50	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
330	83	97	72	0.39	1.04	4.60	1.16	1.35

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	200	50	59	55	0.34	0.63	3.60	0.91	1.06
-30	(-22)	266	67	78	61	0.35	0.83	4.37	1.10	1.28
-25	(-13)	346	87	101	67	0.37	1.09	5.18	1.30	1.52
-20	(- 4)	442	111	130	73	0.39	1.39	6.05	1.52	1.77
-15	(+ 5)	556	140	163	79	0.41	1.75	7.00	1.76	2.05
-10	(+14)	689	174	202	86	0.42	2.17	8.05	2.03	2.36
-5	(+23)	843	212	247	92	0.43	2.66	9.20	2.32	2.70

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	180	45	53	56	0.33	0.56	3.22	0.81	0.94
-30	(-22)	247	62	72	62	0.35	0.77	3.96	1.00	1.16
-25	(-13)	328	83	96	69	0.37	1.03	4.74	1.19	1.39
-20	(- 4)	425	107	124	76	0.40	1.33	5.57	1.40	1.63
-15	(+ 5)	538	136	158	83	0.42	1.69	6.47	1.63	1.89
-10	(+14)	670	169	196	90	0.44	2.11	7.45	1.88	2.18
-5	(+23)	822	207	241	97	0.45	2.60	8.52	2.15	2.50

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	156	39	46	55	0.33	0.49	2.84	0.72	0.83
-30	(-22)	223	56	65	63	0.35	0.70	3.55	0.90	1.04
-25	(-13)	303	76	89	71	0.38	0.95	4.29	1.08	1.26
-20	(- 4)	397	100	116	78	0.41	1.25	5.07	1.28	1.49
-15	(+ 5)	508	128	149	86	0.43	1.60	5.91	1.49	1.73
-10	(+14)	637	161	187	93	0.46	2.01	6.81	1.72	2.00
-5	(+23)	786	198	230	101	0.48	2.49	7.81	1.97	2.29

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	129	33	38	54	0.33	0.41	2.38	0.60	0.70
-30	(-22)	193	49	57	63	0.36	0.61	3.05	0.77	0.89
-25	(-13)	270	68	79	72	0.39	0.85	3.75	0.94	1.10
-20	(- 4)	360	91	106	81	0.42	1.13	4.47	1.13	1.31
-15	(+ 5)	467	118	137	89	0.45	1.47	5.24	1.32	1.53
-10	(+14)	591	149	173	97	0.48	1.86	6.07	1.53	1.78
-5	(+23)	734	185	215	105	0.50	2.32	6.97	1.76	2.04

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted parallel to Base Plate		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		