

COMPRESSOR DEFINITION

| | |
|---------------------------|-----------------|
| Designation | EM Z26CLC |
| Nominal Voltage/Frequency | 220-240 V 50 Hz |
| Engineering Number | 513309021 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|--|-----------------------------------|-------------------------|-----------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-600a | | |
| 3 Nominal voltage and frequency | 220-240 / 50 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSCR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | | Operating voltage range | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | 187 to 255 V | - |
| 8.2 LBP (43°C Ambient temperature) | Static | 187 to 255 V | - |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing pressures/temperature | | | |
| 9.1 Operating (gauge) | 7.7 | [kgf/cm²] (109 psig) | / °C - °F |
| 9.2 Peak (gauge) | 9.8 | [kgf/cm²] (139 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|----------------|----------------------------------|
| 1 Commercial designation | 1/12 | [hp] |
| 2 Displacement | 5.19 | [cm ³] (0.317 cu.in) |
| 2.1 Bore [mm] | 21.000 | |
| 2.2 Stroke [mm] | 15.000 | |
| 3 Lubricant charge | 180 | [ml] (6.09 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ALQUILB / ISO5 | |
| 4 Weight (with oil charge) | 7.88 | [kg] (17.37 lb.) |
| 5 Nitrogen charge | - | [kgf/cm ²] |

C - ELETRICAL DATA

| | | |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50 Hz 1 ~ (Single phase) | |
| 2 Starting device type | PTC | |
| 2.1 Starting device | V230 | |
| 3 Start capacitor | - | [μF(VAC minimum)] |
| 4 Run capacitor | 2.5(380) | [μF(VAC minimum)] |
| 5 Motor protection | T0285/07 | |
| 6 Start winding resistance | 28.90 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 42.70 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (50 Hz) | 2.40 | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50 Hz) | 0.40 | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (50 Hz) | - | [A] - Measured according to UL 984 |
| 11 Approval boards certification | VDE | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|--------------------------------|----------|-----|------------------------------------|--------------------------------------|--|-------------------------------|---|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F)) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 291 | 73 | 85 | 52 | 0.25 | 0.91 | 5.61 | 1.41 | 1.64 |

E - PERFORMANCE - CURVES

| TEST CONDITIONS: | | ASHRAE32 | | | | (Condensing temperature 45°C (+113°F)) | | | | |
|-------------------------|-------|------------------|----------|-----|-------------------|---|---------------|-----------------|-----------|-------|
| @220V50Hz | | Static | | | | | | | | |
| Evaporating temperature | | Cooling capacity | | | Power consumption | Current consumption | Gas flow rate | EFFICIENCY RATE | | |
| | | +/- 5% | | | +/- 5% | +/- 5% | +/- 5% | +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 145 | 37 | 43 | 38 | 0.17 | 0.45 | 3.83 | 0.96 | 1.12 |
| -30 | (-22) | 217 | 55 | 64 | 42 | 0.21 | 0.68 | 5.09 | 1.28 | 1.49 |
| -25 | (-13) | 291 | 73 | 85 | 48 | 0.24 | 0.91 | 6.06 | 1.53 | 1.78 |
| -20 | (- 4) | 375 | 94 | 110 | 54 | 0.27 | 1.18 | 6.91 | 1.74 | 2.03 |
| -15 | (+ 5) | 475 | 120 | 139 | 61 | 0.29 | 1.50 | 7.82 | 1.97 | 2.29 |
| -10 | (+14) | 600 | 151 | 176 | 67 | 0.31 | 1.89 | 8.98 | 2.26 | 2.63 |

| TEST CONDITIONS: @220V50Hz | | ASHRAE32 Static | | | (Condensing temperature 55°C (+131°F)) | | | | | |
|-------------------------------|-------|----------------------------|----------|-----|---|-------------------------------|-------------------------|---------------------------|-----------|-------|
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 112 | 28 | 33 | 36 | 0.17 | 0.35 | 3.07 | 0.77 | 0.90 |
| -30 | (-22) | 187 | 47 | 55 | 42 | 0.21 | 0.59 | 4.37 | 1.10 | 1.28 |
| -25 | (-13) | 263 | 66 | 77 | 50 | 0.25 | 0.83 | 5.31 | 1.34 | 1.56 |
| -20 | (- 4) | 347 | 88 | 102 | 57 | 0.28 | 1.09 | 6.08 | 1.53 | 1.78 |
| -15 | (+ 5) | 447 | 113 | 131 | 65 | 0.31 | 1.41 | 6.86 | 1.73 | 2.01 |
| -10 | (+14) | 569 | 144 | 167 | 72 | 0.34 | 1.80 | 7.84 | 1.97 | 2.30 |

| TEST CONDITIONS: | | ASHRAE32 | | | (Condensing temperature 65°C (+149°F)) | | | | | |
|-------------------------|-------|------------------|----------|-----|---|---------------------|---------------|-----------------|-----------|-------|
| @220V50Hz | | Static | | | | | | | | |
| Evaporating temperature | | Cooling capacity | | | Power consumption | Current consumption | Gas flow rate | EFFICIENCY RATE | | |
| | | +/- 5% | | | +/- 5% | +/- 5% | +/- 5% | +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 79 | 20 | 23 | 34 | 0.15 | 0.25 | 2.33 | 0.59 | 0.68 |
| -30 | (-22) | 157 | 39 | 46 | 42 | 0.20 | 0.49 | 3.68 | 0.93 | 1.08 |
| -25 | (-13) | 234 | 59 | 69 | 50 | 0.25 | 0.74 | 4.63 | 1.17 | 1.36 |
| -20 | (- 4) | 318 | 80 | 93 | 60 | 0.29 | 1.00 | 5.35 | 1.35 | 1.57 |
| -15 | (+ 5) | 417 | 105 | 122 | 69 | 0.33 | 1.31 | 6.04 | 1.52 | 1.77 |
| -10 | (+14) | 537 | 135 | 157 | 78 | 0.36 | 1.69 | 6.87 | 1.73 | 2.01 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|------------------------------|------|--------------------------|
| 1 Base plate | European Standard EUEM | | |
| 2 Tray holder | Yes | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Slanted 42° up + 45° to Back | | |
| 3.2 DISCHARGE | 5.1 +0.10/+0.00 | [mm] | (0.201" +0.004"/+0.000") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Slanted 42° up + 24° to Back | | |
| 3.3 PROCESS | 6 +0.08/-0.08 | [mm] | (0.236" +0.003"/-0.003") |
| 3.3.1 Material | Copper(OD) | | |
| 3.3.2 Shape | Slanted 43° up + 45° to Back | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |