

COMPRESSOR DEFINITION

Designation	EM Z26CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513309013

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	187 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	187 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	7.7	[kgf/cm ²] (109 psig)	/ °C - °F
9.2 Peak (gauge)	9.8	[kgf/cm ²] (139 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/12	[hp]
2 Displacement	5.19	[cm ³] (0.317 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.88	[kg] (17.37 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	V230	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	2.5(380)	[µF(VAC minimum)]
5 Motor protection	T0285/07	
6 Start winding resistance	28.90	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	42.70	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	2.40	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.40	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
291	73	85	52	0.25	0.91	5.61	1.41	1.64

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	145	37	43	38	0.17	0.45	3.83	0.96	1.12
-30 (-22)	217	55	64	42	0.21	0.68	5.09	1.28	1.49
-25 (-13)	291	73	85	48	0.24	0.91	6.06	1.53	1.78
-20 (- 4)	375	94	110	54	0.27	1.18	6.91	1.74	2.03
-15 (+ 5)	475	120	139	61	0.29	1.50	7.82	1.97	2.29
-10 (+14)	600	151	176	67	0.31	1.89	8.98	2.26	2.63

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	112	28	33	36	0.17	0.35	3.07	0.77	0.90
-30 (-22)	187	47	55	42	0.21	0.59	4.37	1.10	1.28
-25 (-13)	263	66	77	50	0.25	0.83	5.31	1.34	1.56
-20 (- 4)	347	88	102	57	0.28	1.09	6.08	1.53	1.78
-15 (+ 5)	447	113	131	65	0.31	1.41	6.86	1.73	2.01
-10 (+14)	569	144	167	72	0.34	1.80	7.84	1.97	2.30

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	79	20	23	34	0.15	0.25	2.33	0.59	0.68
-30 (-22)	157	39	46	42	0.20	0.49	3.68	0.93	1.08
-25 (-13)	234	59	69	50	0.25	0.74	4.63	1.17	1.36
-20 (- 4)	318	80	93	60	0.29	1.00	5.35	1.35	1.57
-15 (+ 5)	417	105	122	69	0.33	1.31	6.04	1.52	1.77
-10 (+14)	537	135	157	78	0.36	1.69	6.87	1.73	2.01

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 42° up + 24° to Back		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 43° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		