

COMPRESSOR DEFINITION

| | |
|---------------------------|-------------|
| Designation | EG U80HLC |
| Nominal Voltage/Frequency | 115 V 60 Hz |
| Engineering Number | 513700183 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|--|-----------------------------------|-----------------------------------|-------------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-134a | | |
| 3 Nominal voltage and frequency | 115 / 60 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSCR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | Operating voltage range | | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | - | 98 to 140 V |
| 8.2 LBP (43°C Ambient temperature) | Static | - | 98 to 140 V |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing pressures/temperature | | | |
| 9.1 Operating (gauge) | 16.2 | [kgf/cm ²] (230 psig) | / °C - °F |
| 9.2 Peak (gauge) | 20.6 | [kgf/cm ²] (293 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|---------------|--|
| 1 Commercial designation | 1/4 | [hp] |
| 2 Displacement | 7.15 | [cm ³] (0.436 cu.in) |
| 2.1 Bore [mm] | 22.500 | |
| 2.2 Stroke [mm] | 18.000 | |
| 3 Lubricant charge | 280 | [ml] (9.47 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ESTER / ISO10 | |
| 4 Weight (with oil charge) | 11.18 | [kg] (24.65 lb.) |
| 5 Nitrogen charge | 0.2 to 0.3 | [kgf/cm ²] (2.84 to 4.27 psig) |

C - ELETRICAL DATA

| | | |
|--|---|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 115 V 60 Hz 1 ~ (Single phase) | |
| 2 Starting device type | PTC | |
| 2.1 Starting device | 490D314R7/7M4R7MD3/8EA14C3/8EA1B3/8EA21C3/8EA3B3/ | |
| 3 Start capacitor | - | [µF(VAC minimum)] |
| 4 Run capacitor | 20(180) | [µF(VAC minimum)] |
| 5 Motor protection | 4TM 445LFBYY-53 | |
| 6 Start winding resistance | 3.15 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 3.05 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (60 Hz) | 14.50 | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (60 Hz) | 2.30 | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (60 Hz) | - | [A] - Measured according to UL 984 |
| 11 Approval boards certification | UL | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | | |
|-------------------------------|----------|-----|--------------------------------|----------------------------------|--|---------------------------|--|-------|--|
| TEST CONDITIONS: @115V60Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] | |
| 820 | 207 | 240 | 148 | 1.28 | 4.66 | 5.55 | 1.40 | 1.63 | |

| | | | | | | | | | |
|-------------------------------|----------|-----|--------------------------------|----------------------------------|--|---------------------------|--|-------|--|
| TEST CONDITIONS: @115V60Hz | | | ASHRAELBP32 Fan | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] | |
| 820 | 207 | 240 | 148 | 1.28 | 4.66 | 5.55 | 1.40 | 1.63 | |

E - PERFORMANCE - CURVES

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @115V60Hz | | | ASHRAE32 Static | | (Condensing temperature 45°C (+113°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 439 | 111 | 129 | 98 | 0.86 | 2.48 | 4.49 | 1.13 | 1.31 |
| -30 (-22) | 609 | 154 | 178 | 116 | 1.03 | 3.45 | 5.25 | 1.32 | 1.54 |
| -25 (-13) | 816 | 206 | 239 | 136 | 1.19 | 4.63 | 6.01 | 1.51 | 1.76 |
| -20 (- 4) | 1072 | 270 | 314 | 157 | 1.37 | 6.10 | 6.81 | 1.72 | 1.99 |
| -15 (+ 5) | 1391 | 351 | 408 | 180 | 1.56 | 7.94 | 7.70 | 1.94 | 2.26 |
| -10 (+14) | 1785 | 450 | 523 | 204 | 1.77 | 10.23 | 8.73 | 2.20 | 2.56 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @115V60Hz | | | ASHRAE32 Static | | (Condensing temperature 55°C (+131°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 359 | 90 | 105 | 95 | 0.84 | 2.03 | 3.78 | 0.95 | 1.11 |
| -30 (-22) | 534 | 134 | 156 | 117 | 1.03 | 3.02 | 4.54 | 1.14 | 1.33 |
| -25 (-13) | 738 | 186 | 216 | 140 | 1.22 | 4.19 | 5.27 | 1.33 | 1.54 |
| -20 (- 4) | 986 | 248 | 289 | 165 | 1.43 | 5.61 | 6.00 | 1.51 | 1.76 |
| -15 (+ 5) | 1289 | 325 | 378 | 190 | 1.64 | 7.36 | 6.78 | 1.71 | 1.99 |
| -10 (+14) | 1661 | 418 | 487 | 217 | 1.88 | 9.51 | 7.66 | 1.93 | 2.24 |

E - PERFORMANCE - CURVES

| TEST CONDITIONS: @115V60Hz | | ASHRAE32 Static | | | (Condensing temperature 65°C (+149°F)) | | | | | |
|-------------------------------|-------|----------------------------|----------|-----|---|-------------------------------|-------------------------|---------------------------|-----------|-------|
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 266 | 67 | 78 | 83 | 0.76 | 1.51 | 3.23 | 0.81 | 0.95 |
| -30 | (-22) | 447 | 113 | 131 | 111 | 0.98 | 2.53 | 3.98 | 1.00 | 1.17 |
| -25 | (-13) | 651 | 164 | 191 | 140 | 1.21 | 3.70 | 4.64 | 1.17 | 1.36 |
| -20 | (- 4) | 891 | 225 | 261 | 169 | 1.45 | 5.07 | 5.28 | 1.33 | 1.55 |
| -15 | (+ 5) | 1180 | 297 | 346 | 200 | 1.70 | 6.74 | 5.93 | 1.49 | 1.74 |
| -10 | (+14) | 1531 | 386 | 449 | 231 | 1.97 | 8.77 | 6.64 | 1.67 | 1.95 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|-------------------------------|------|--------------------------|
| 1 Base plate | Universal EG/F/AMEM version 2 | | |
| 2 Tray holder | No | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Straight | | |
| 3.2 DISCHARGE | 4.94 +0.08/-0.08 | [mm] | (0.194" +0.003"/-0.003") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Straight | | |
| 3.3 PROCESS | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.3.1 Material | Copper | | |
| 3.3.2 Shape | Straight | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |