

### COMPRESSOR DEFINITION

Designation	J 7238E
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	163AA01

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-22		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Air Conditioning		
4.1 Evaporating temperature range	0°C to 15°C	(32°F to 59°F)	
5 Motor type	PSC		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	21.7	[kgf/cm <sup>2</sup> ] (309 psig)	/ °C - °F
9.2 Peak (gauge)	24.2	[kgf/cm <sup>2</sup> ] (344 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1 1/2	[hp]
2 Displacement	32.67	[cm <sup>3</sup> ] (1.994 cu.in)
2.1 Bore [mm]	41.770	
2.2 Stroke [mm]	23.850	
3 Lubricant charge	890	[ml] (30.10 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	MINERAL / ISO32	
4 Weight (with oil charge)	21.5	[kg] (47.40 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PSC	
2.1 Starting device		
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	25(450)	[µF(VAC minimum)]
5 Motor protection	CRA9951-3031	
6 Start winding resistance	5.45	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.30	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	51.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	10.50	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification		

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			<b>ASHRAEHBP46</b> Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
15108	3807	4427	1959	10.28	93.31	7.71	1.94	2.26

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			<b>ASHRAE46</b> Fan		(Condensing temperature 35°C (+95°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0 (+32)	16285	4104	4772	1440	8.35	0.00	11.31	2.85	3.31
+5 (+41)	19186	4835	5622	1517	8.56	0.00	12.65	3.19	3.71
+10 (+50)	22762	5736	6670	1593	8.77	0.00	14.28	3.60	4.19
+15 (+59)	27011	6807	7915	1669	8.99	0.00	16.19	4.08	4.74

TEST CONDITIONS: @220V50Hz			<b>ASHRAE46</b> Fan		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0 (+32)	13884	3499	4068	1597	8.99	0.00	8.69	2.19	2.55
+5 (+41)	16572	4176	4856	1705	9.32	0.00	9.72	2.45	2.85
+10 (+50)	19875	5009	5824	1806	9.59	0.00	11.01	2.77	3.23
+15 (+59)	23795	5996	6972	1898	9.81	0.00	12.53	3.16	3.67

TEST CONDITIONS: @220V50Hz			<b>ASHRAE46</b> Fan		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0 (+32)	11385	2869	3336	1761	9.66	0.00	6.47	1.63	1.89
+5 (+41)	13848	3490	4058	1902	10.11	0.00	7.28	1.83	2.13
+10 (+50)	16868	4251	4943	2027	10.45	0.00	8.32	2.10	2.44
+15 (+59)	20445	5152	5991	2136	10.67	0.00	9.57	2.41	2.80

### F - EXTERNAL CHARACTERISTICS

1 Base plate	American Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	12.77 +0.08/+0.00	[mm]	(0.503" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	8 +0.07/+0.00	[mm]	(0.315" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted J		
3.3 PROCESS	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		