

### COMPRESSOR DEFINITION

Designation	EM Y40CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	894LA57

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low-Medium Back Pressure		
4.1 Evaporating temperature range	-35°C to -5°C	(-31°F to 23°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	7.7	[kgf/cm <sup>2</sup> ] (109 psig)	/ °C - °F
9.2 Peak (gauge)	9.8	[kgf/cm <sup>2</sup> ] (139 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	7.23	[cm <sup>3</sup> ] (0.441 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	16.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	MINERAL / ISO7	
4 Weight (with oil charge)	7.7	[kg] (16.98 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	2019	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(450)	[µF(VAC minimum)]
5 Motor protection	AD37FN10	
6 Start winding resistance	29.90	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	35.28	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	2.70	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.34	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
414	104	121	79	0.37	1.30	5.23	1.32	1.53

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	247	62	72	55	0.26	0.77	4.48	1.13	1.31
-30	(-22)	330	83	97	62	0.29	1.03	5.33	1.34	1.56
-25	(-13)	431	109	126	69	0.32	1.35	6.25	1.57	1.83
-20	(- 4)	552	139	162	76	0.35	1.73	7.24	1.82	2.12
-15	(+ 5)	696	175	204	84	0.38	2.19	8.30	2.09	2.43
-10	(+14)	863	218	253	92	0.41	2.72	9.42	2.37	2.76
-5	(+23)	1058	267	310	100	0.45	3.35	10.61	2.67	3.11

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	230	58	67	55	0.27	0.72	4.17	1.05	1.22
-30	(-22)	311	78	91	64	0.30	0.97	4.89	1.23	1.43
-25	(-13)	409	103	120	72	0.33	1.28	5.67	1.43	1.66
-20	(- 4)	527	133	154	81	0.37	1.66	6.50	1.64	1.90
-15	(+ 5)	667	168	195	90	0.41	2.10	7.38	1.86	2.16
-10	(+14)	831	209	243	100	0.45	2.62	8.30	2.09	2.43
-5	(+23)	1021	257	299	110	0.49	3.23	9.27	2.33	2.71

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	203	51	59	55	0.27	0.64	3.68	0.93	1.08
-30	(-22)	281	71	82	65	0.30	0.88	4.32	1.09	1.26
-25	(-13)	376	95	110	75	0.34	1.18	4.99	1.26	1.46
-20	(- 4)	489	123	143	86	0.38	1.54	5.70	1.44	1.67
-15	(+ 5)	625	157	183	97	0.43	1.97	6.44	1.62	1.89
-10	(+14)	784	197	230	109	0.48	2.47	7.20	1.82	2.11
-5	(+23)	969	244	284	121	0.54	3.06	7.99	2.01	2.34

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	176	44	52	55	0.27	0.55	3.16	0.80	0.93
-30	(-22)	250	63	73	66	0.31	0.78	3.75	0.95	1.10
-25	(-13)	341	86	100	78	0.36	1.07	4.36	1.10	1.28
-20	(- 4)	450	113	132	90	0.41	1.41	4.99	1.26	1.46
-15	(+ 5)	580	146	170	103	0.46	1.83	5.63	1.42	1.65
-10	(+14)	733	185	215	117	0.52	2.31	6.27	1.58	1.84
-5	(+23)	912	230	267	132	0.59	2.89	6.92	1.74	2.03

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		