

COMPRESSOR DEFINITION

Designation	EM U32CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	893BA75

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low-Medium Back Pressure		
4.1 Evaporating temperature range	-35°C to -5°C	(-31°F to 23°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	7.7	[kgf/cm ²] (109 psig)	/ °C - °F
9.2 Peak (gauge)	9.8	[kgf/cm ²] (139 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	5.96	[cm ³] (0.364 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	MINERAL / ISO7	
4 Weight (with oil charge)	7.1	[kg] (15.65 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	TSD-220V	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(380)	[µF(VAC minimum)]
5 Motor protection	4TM110NFBYY-53	
6 Start winding resistance	28.30	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	38.90	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	2.50	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.44	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
330	83	97	66	0.31	1.04	5.04	1.27	1.48

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	200	50	59	50	0.24	0.63	4.02	1.01	1.18
-30	(-22)	266	67	78	54	0.26	0.83	4.89	1.23	1.43
-25	(-13)	346	87	101	60	0.28	1.09	5.80	1.46	1.70
-20	(- 4)	442	111	130	65	0.30	1.39	6.77	1.71	1.99
-15	(+ 5)	556	140	163	71	0.33	1.75	7.83	1.97	2.29
-10	(+14)	689	174	202	77	0.36	2.17	8.98	2.26	2.63
-5	(+23)	843	212	247	82	0.38	2.66	10.24	2.58	3.00

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	180	45	53	50	0.24	0.56	3.63	0.91	1.06
-30	(-22)	247	62	72	56	0.26	0.77	4.45	1.12	1.30
-25	(-13)	328	83	96	62	0.29	1.03	5.28	1.33	1.55
-20	(- 4)	425	107	124	69	0.32	1.33	6.14	1.55	1.80
-15	(+ 5)	538	136	158	76	0.35	1.69	7.04	1.78	2.06
-10	(+14)	670	169	196	84	0.38	2.11	8.02	2.02	2.35
-5	(+23)	822	207	241	91	0.41	2.60	9.07	2.29	2.66

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	156	39	46	49	0.24	0.49	3.19	0.80	0.93
-30	(-22)	223	56	65	56	0.27	0.70	3.97	1.00	1.16
-25	(-13)	303	76	89	64	0.30	0.95	4.74	1.19	1.39
-20	(- 4)	397	100	116	72	0.33	1.25	5.50	1.39	1.61
-15	(+ 5)	508	128	149	81	0.37	1.60	6.28	1.58	1.84
-10	(+14)	637	161	187	90	0.41	2.01	7.09	1.79	2.08
-5	(+23)	786	198	230	99	0.45	2.49	7.95	2.00	2.33

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	129	33	38	47	0.23	0.41	2.73	0.69	0.80
-30	(-22)	193	49	57	55	0.26	0.61	3.50	0.88	1.03
-25	(-13)	270	68	79	64	0.30	0.85	4.22	1.06	1.24
-20	(- 4)	360	91	106	74	0.34	1.13	4.90	1.23	1.44
-15	(+ 5)	467	118	137	84	0.39	1.47	5.56	1.40	1.63
-10	(+14)	591	149	173	95	0.43	1.86	6.23	1.57	1.83
-5	(+23)	734	185	215	106	0.48	2.32	6.92	1.74	2.03

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	5.02 +0.02/-0.02	[mm]	(0.198" +0.001"/-0.001")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		