

COMPRESSOR DEFINITION

| | |
|---------------------------|------------------------|
| Designation | EM U26CLC |
| Nominal Voltage/Frequency | 220-240 V 50 Hz |
| Engineering Number | 895HA95 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|------------------------------------|-----------------------------------|-----------------------------------|-----------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-600a | | |
| 3 Nominal voltage and frequency | 220-240 / 50 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSIR-RSCR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | | Operating voltage range | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | 198 to 254 V | - |
| 8.2 LBP (43°C Ambient temperature) | Static | 198 to 254 V | - |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing temperature | | | |
| 9.1 Operating | 6.9 | [kgf/cm ²] (98 psig) | / °C - °F |
| 9.2 Peak | 7.8 | [kgf/cm ²] (111 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|----------------|----------------------------------|
| 1 Commercial designation | | [hp] |
| 2 Displacement | 5.19 | [cm ³] (0.317 cu.in) |
| 2.1 Bore [mm] | 21.000 | |
| 2.2 Stroke [mm] | 15.000 | |
| 3 Lubricant charge | 180 | [ml] (6.09 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ALQUILB / ISO5 | |
| 4 Weight (with oil charge) | 6.8 | [kg] (14.99 lb.) |
| 5 Nitrogen charge | - | [kgf/cm ²] |

C - ELETRICAL DATA

| | | |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50 Hz 1 ~ (Single phase) | |
| 2 Starting device type | PTC | |
| 2.1 Starting device | V230 | |
| 3 Start capacitor | - | [μF(VAC minimum)] |
| 4 Run capacitor | 4(440) | [μF(VAC minimum)] |
| 5 Motor protection | T0879/07 | |
| 6 Start winding resistance | 24.60 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 43.55 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (50 Hz) | 2.45 | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50 Hz) | 0.38 | [A] |
| 10 FLA - Full Load Amperage HBP (50 Hz) | - | [A] |
| 11 Approval boards certification | CCC - VDE | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|-------------------------------|----------|-----|-----------------------------|-------------------------------|--|---------------------------|--|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 280 | 71 | 82 | 58 | 0.30 | 0.88 | 4.84 | 1.22 | 1.42 |

E - PERFORMANCE - CURVES

| | | | | | | | | | | |
|-------------------------------|-------|----------------------------|--------------------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 45°C (+113°F)) | | | | | |
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 128 | 32 | 38 | 41 | 0.28 | 0.40 | 3.12 | 0.79 | 0.91 |
| -30 | (-22) | 202 | 51 | 59 | 48 | 0.29 | 0.63 | 4.21 | 1.06 | 1.23 |
| -25 | (-13) | 276 | 70 | 81 | 54 | 0.29 | 0.87 | 5.11 | 1.29 | 1.50 |
| -20 | (- 4) | 357 | 90 | 105 | 61 | 0.30 | 1.12 | 5.90 | 1.49 | 1.73 |
| -15 | (+ 5) | 452 | 114 | 133 | 68 | 0.31 | 1.42 | 6.69 | 1.69 | 1.96 |
| -10 | (+14) | 571 | 144 | 167 | 75 | 0.32 | 1.80 | 7.59 | 1.91 | 2.22 |

| | | | | | | | | | | |
|-------------------------------|-------|----------------------------|--------------------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 55°C (+131°F)) | | | | | |
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 102 | 26 | 30 | 40 | 0.28 | 0.32 | 2.54 | 0.64 | 0.74 |
| -30 | (-22) | 179 | 45 | 53 | 48 | 0.29 | 0.56 | 3.69 | 0.93 | 1.08 |
| -25 | (-13) | 255 | 64 | 75 | 55 | 0.30 | 0.80 | 4.59 | 1.16 | 1.34 |
| -20 | (- 4) | 336 | 85 | 98 | 63 | 0.31 | 1.06 | 5.33 | 1.34 | 1.56 |
| -15 | (+ 5) | 431 | 109 | 126 | 71 | 0.32 | 1.36 | 6.03 | 1.52 | 1.77 |
| -10 | (+14) | 548 | 138 | 160 | 80 | 0.33 | 1.73 | 6.77 | 1.71 | 1.99 |

| | | | | | | | | | | |
|-------------------------------|-------|----------------------------|--------------------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 65°C (+149°F)) | | | | | |
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 74 | 19 | 22 | 40 | 0.28 | 0.23 | 1.87 | 0.47 | 0.55 |
| -30 | (-22) | 152 | 38 | 44 | 48 | 0.30 | 0.48 | 3.05 | 0.77 | 0.89 |
| -25 | (-13) | 226 | 57 | 66 | 57 | 0.31 | 0.71 | 3.93 | 0.99 | 1.15 |
| -20 | (- 4) | 306 | 77 | 90 | 67 | 0.32 | 0.96 | 4.61 | 1.16 | 1.35 |
| -15 | (+ 5) | 397 | 100 | 116 | 77 | 0.33 | 1.25 | 5.18 | 1.31 | 1.52 |
| -10 | (+14) | 510 | 128 | 149 | 88 | 0.35 | 1.61 | 5.76 | 1.45 | 1.69 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|-------------------|------|--------------------------|
| 1 Base plate | European Standard | | |
| 2 Tray holder | Yes | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Slanted 42° | | |
| 3.2 DISCHARGE | 5.1 +0.10/+0.00 | [mm] | (0.201" +0.004"/+0.000") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Straight | | |
| 3.3 PROCESS | 6 +0.08/-0.08 | [mm] | (0.236" +0.003"/-0.003") |
| 3.3.1 Material | Copper(OD) | | |
| 3.3.2 Shape | Slanted 42° | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |