

COMPRESSOR DEFINITION

Designation	EM X46CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	898EA95

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	7.96	[cm ³] (0.486 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	17.600	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.8	[kg] (17.20 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	TSD-220V0.6	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(440)	[µF(VAC minimum)]
5 Motor protection	4TM189KFBYY-73	
6 Start winding resistance	17.80	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	25.00	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	3.80	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.22	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	IRAM - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
461	116	135	78	0.36	1.45	5.88	1.48	1.72

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	228	57	67	53	0.25	0.71	4.30	1.08	1.26
-30	(-22)	326	82	96	62	0.29	1.02	5.24	1.32	1.54
-25	(-13)	442	111	129	71	0.34	1.39	6.19	1.56	1.81
-20	(- 4)	577	145	169	81	0.38	1.81	7.14	1.80	2.09
-15	(+ 5)	735	185	216	91	0.43	2.31	8.11	2.04	2.38
-10	(+14)	920	232	270	101	0.48	2.90	9.13	2.30	2.67

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	213	54	62	53	0.25	0.67	3.98	1.00	1.17
-30	(-22)	307	77	90	64	0.30	0.96	4.78	1.20	1.40
-25	(-13)	417	105	122	75	0.35	1.31	5.56	1.40	1.63
-20	(- 4)	548	138	161	86	0.40	1.72	6.35	1.60	1.86
-15	(+ 5)	701	177	206	98	0.46	2.21	7.15	1.80	2.09
-10	(+14)	881	222	258	110	0.52	2.78	7.97	2.01	2.34

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	189	48	55	52	0.25	0.59	3.64	0.92	1.07
-30	(-22)	283	71	83	65	0.30	0.89	4.36	1.10	1.28
-25	(-13)	393	99	115	78	0.36	1.23	5.06	1.28	1.48
-20	(- 4)	522	132	153	91	0.42	1.64	5.75	1.45	1.68
-15	(+ 5)	674	170	198	105	0.49	2.12	6.44	1.62	1.89
-10	(+14)	851	215	250	119	0.56	2.69	7.15	1.80	2.10

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		