

COMPRESSOR DEFINITION

Designation	EM Y55CLP
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	897GA93

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR-RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	9.04	[cm ³] (0.552 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.7	[kg] (16.98 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	MI2021	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	4(440)	[μF(VAC minimum)]
5 Motor protection	AE18BQ10	
6 Start winding resistance	27.35	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	20.40	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	4.75	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.50	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification		

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
533	134	156	97	0.47	1.67	5.52	1.39	1.62

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	288	73	84	66	0.31	0.90	4.35	1.10	1.28
-30	(-22)	382	96	112	77	0.37	1.20	4.97	1.25	1.46
-25	(-13)	506	128	148	89	0.42	1.59	5.69	1.43	1.67
-20	(- 4)	661	167	194	102	0.47	2.08	6.50	1.64	1.91
-15	(+ 5)	846	213	248	114	0.52	2.66	7.37	1.86	2.16
-10	(+14)	1060	267	311	128	0.57	3.34	8.29	2.09	2.43

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	262	66	77	67	0.31	0.82	3.90	0.98	1.14
-30	(-22)	360	91	105	79	0.38	1.13	4.54	1.14	1.33
-25	(-13)	486	122	142	92	0.44	1.52	5.24	1.32	1.54
-20	(- 4)	639	161	187	106	0.50	2.01	5.98	1.51	1.75
-15	(+ 5)	819	206	240	121	0.56	2.58	6.73	1.70	1.97
-10	(+14)	1025	258	300	137	0.62	3.24	7.48	1.88	2.19

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	235	59	69	68	0.31	0.74	3.48	0.88	1.02
-30	(-22)	335	84	98	81	0.39	1.05	4.15	1.05	1.22
-25	(-13)	460	116	135	95	0.46	1.44	4.84	1.22	1.42
-20	(- 4)	609	154	179	111	0.52	1.92	5.51	1.39	1.62
-15	(+ 5)	782	197	229	128	0.59	2.46	6.15	1.55	1.80
-10	(+14)	979	247	287	146	0.67	3.09	6.74	1.70	1.97

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		