

COMPRESSOR DEFINITION

Designation	NB U1114Y
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	853BA12

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	7.7	[kgf/cm ²] (109 psig)	/ °C - °F
9.2 Peak (gauge)	9.8	[kgf/cm ²] (139 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	9.99	[cm ³] (0.610 cu.in)
2.1 Bore [mm]	26.497	
2.2 Stroke [mm]	18.120	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	10.2	[kg] (22.49 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	V230	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(450)	[µF(VAC minimum)]
5 Motor protection	T0133/07	
6 Start winding resistance	19.70	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	19.60	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	4.40	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.45	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	CCIB - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
577	145	169	104	0.47	1.81	5.56	1.40	1.63

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	334	84	98	71	0.33	1.05	4.68	1.18	1.37
-30	(-22)	444	112	130	78	0.37	1.39	5.33	1.34	1.56
-25	(-13)	576	145	169	91	0.41	1.81	5.97	1.50	1.75
-20	(- 4)	735	185	215	103	0.45	2.31	7.15	1.80	2.10
-15	(+ 5)	925	233	271	108	0.50	2.91	9.46	2.38	2.77
-10	(+14)	1151	290	337	99	0.54	3.63	13.44	3.39	3.94

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	312	79	91	73	0.34	0.98	4.51	1.14	1.32
-30	(-22)	421	106	124	80	0.39	1.32	5.20	1.31	1.52
-25	(-13)	551	139	161	95	0.44	1.73	5.48	1.38	1.61
-20	(- 4)	705	178	207	110	0.49	2.21	5.92	1.49	1.73
-15	(+ 5)	887	224	260	121	0.54	2.79	7.07	1.78	2.07
-10	(+14)	1104	278	323	120	0.60	3.48	9.51	2.40	2.79

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	282	71	83	70	0.33	0.88	4.18	1.05	1.23
-30	(-22)	395	99	116	79	0.39	1.24	5.26	1.33	1.54
-25	(-13)	525	132	154	96	0.45	1.65	5.53	1.39	1.62
-20	(- 4)	677	171	198	117	0.51	2.13	5.56	1.40	1.63
-15	(+ 5)	855	216	251	134	0.58	2.69	5.90	1.49	1.73
-10	(+14)	1064	268	312	142	0.65	3.36	7.14	1.80	2.09

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	222	56	65	70	0.33	0.70	2.81	0.71	0.82
-30	(-22)	341	86	100	81	0.39	1.07	4.62	1.16	1.35
-25	(-13)	476	120	139	103	0.46	1.49	5.22	1.31	1.53
-20	(- 4)	629	159	184	130	0.54	1.98	5.18	1.30	1.52
-15	(+ 5)	806	203	236	156	0.62	2.54	5.06	1.28	1.48
-10	(+14)	1012	255	296	174	0.70	3.19	5.44	1.37	1.59

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		