

COMPRESSOR DEFINITION

| | |
|---------------------------|-----------------|
| Designation | EG Y100HLC |
| Nominal Voltage/Frequency | 220-240 V 50 Hz |
| Engineering Number | 513700116 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|--|-----------------------------------|-----------------------------------|-----------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-134a | | |
| 3 Nominal voltage and frequency | 220-240 / 50 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSCR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | Operating voltage range | | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | 198 to 255 V | - |
| 8.2 LBP (43°C Ambient temperature) | Static | 198 to 255 V | - |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing pressures/temperature | | | |
| 9.1 Operating (gauge) | 16.2 | [kgf/cm ²] (230 psig) | / °C - °F |
| 9.2 Peak (gauge) | 20.6 | [kgf/cm ²] (293 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|---------------|--|
| 1 Commercial designation | 1/3 | [hp] |
| 2 Displacement | 8.59 | [cm ³] (0.524 cu.in) |
| 2.1 Bore [mm] | 24.000 | |
| 2.2 Stroke [mm] | 19.000 | |
| 3 Lubricant charge | 280 | [ml] (9.47 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ESTER / ISO10 | |
| 4 Weight (with oil charge) | 11.33 | [kg] (24.98 lb.) |
| 5 Nitrogen charge | 0.2 to 0.3 | [kgf/cm ²] (2.84 to 4.27 psig) |

C - ELETRICAL DATA

| | | |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50 Hz 1 ~ (Single phase) | |
| 2 Starting device type | PTC | |
| 2.1 Starting device | 2019 | |
| 3 Start capacitor | - | [µF(VAC minimum)] |
| 4 Run capacitor | 5(350) | [µF(VAC minimum)] |
| 5 Motor protection | AD22FQX | |
| 6 Start winding resistance | 21.40 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 15.50 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (50 Hz) | 6.20 | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50 Hz) | 0.95 | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (50 Hz) | - | [A] - Measured according to UL 984 |
| 11 Approval boards certification | | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|-------------------------------|----------|-----|-----------------------------|-------------------------------|--|---------------------------|--|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 875 | 221 | 256 | 155 | 0.73 | 4.97 | 5.63 | 1.42 | 1.65 |

E - PERFORMANCE - CURVES

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|-----------------------------|--|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 45°C (+113°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 446 | 112 | 131 | 100 | 0.46 | 2.52 | 4.48 | 1.13 | 1.31 |
| -30 (-22) | 643 | 162 | 188 | 120 | 0.56 | 3.64 | 5.32 | 1.34 | 1.56 |
| -25 (-13) | 861 | 217 | 252 | 141 | 0.65 | 4.89 | 6.10 | 1.54 | 1.79 |
| -20 (- 4) | 1116 | 281 | 327 | 163 | 0.75 | 6.35 | 6.88 | 1.73 | 2.01 |
| -15 (+ 5) | 1427 | 359 | 418 | 185 | 0.85 | 8.14 | 7.70 | 1.94 | 2.26 |
| -10 (+14) | 1808 | 456 | 530 | 209 | 0.96 | 10.36 | 8.63 | 2.17 | 2.53 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|-----------------------------|--|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 55°C (+131°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 399 | 101 | 117 | 99 | 0.46 | 2.26 | 4.04 | 1.02 | 1.18 |
| -30 (-22) | 586 | 148 | 172 | 122 | 0.56 | 3.32 | 4.78 | 1.20 | 1.40 |
| -25 (-13) | 792 | 200 | 232 | 146 | 0.67 | 4.50 | 5.43 | 1.37 | 1.59 |
| -20 (- 4) | 1035 | 261 | 303 | 171 | 0.79 | 5.89 | 6.05 | 1.52 | 1.77 |
| -15 (+ 5) | 1331 | 335 | 390 | 199 | 0.91 | 7.60 | 6.69 | 1.68 | 1.96 |
| -10 (+14) | 1698 | 428 | 498 | 229 | 1.05 | 9.73 | 7.39 | 1.86 | 2.17 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|-----------------------------|--|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 65°C (+149°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 330 | 83 | 97 | 93 | 0.43 | 1.87 | 3.54 | 0.89 | 1.04 |
| -30 (-22) | 507 | 128 | 149 | 119 | 0.55 | 2.87 | 4.22 | 1.06 | 1.24 |
| -25 (-13) | 702 | 177 | 206 | 147 | 0.68 | 3.98 | 4.79 | 1.21 | 1.40 |
| -20 (- 4) | 932 | 235 | 273 | 177 | 0.82 | 5.31 | 5.29 | 1.33 | 1.55 |
| -15 (+ 5) | 1215 | 306 | 356 | 211 | 0.97 | 6.94 | 5.78 | 1.46 | 1.69 |
| -10 (+14) | 1568 | 395 | 459 | 248 | 1.14 | 8.98 | 6.31 | 1.59 | 1.85 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|-------------------------------|------|--------------------------|
| 1 Base plate | Universal EG/F/AMEM version 2 | | |
| 2 Tray holder | Yes | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Straight | | |
| 3.2 DISCHARGE | 4.94 +0.08/-0.08 | [mm] | (0.194" +0.003"/-0.003") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Straight | | |
| 3.3 PROCESS | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.3.1 Material | Copper | | |
| 3.3.2 Shape | Straight | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |