

### COMPRESSOR DEFINITION

Designation	EM X70CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513309507

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	7.7	[kgf/cm <sup>2</sup> ] (109 psig)	/ °C - °F
9.2 Peak (gauge)	9.8	[kgf/cm <sup>2</sup> ] (139 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	11.14	[cm <sup>3</sup> ] (0.680 cu.in)
2.1 Bore [mm]	26.000	
2.2 Stroke [mm]	21.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	8.6	[kg] (18.96 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	TSD-220V	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	5(300)	[µF(VAC minimum)]
5 Motor protection	4TM276KFBYY-73	
6 Start winding resistance	14.10	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	18.80	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	4.90	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.85	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	IRAM - VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
652	164	191	111	0.55	2.05	5.87	1.48	1.72

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	389	98	114	85	0.46	1.22	4.57	1.15	1.34
-30 (-22)	488	123	143	91	0.44	1.53	5.35	1.35	1.57
-25 (-13)	621	156	182	103	0.48	1.95	6.07	1.53	1.78
-20 (- 4)	789	199	231	117	0.56	2.48	6.75	1.70	1.98
-15 (+ 5)	995	251	292	134	0.65	3.13	7.42	1.87	2.17
-10 (+14)	1241	313	364	153	0.75	3.91	8.12	2.05	2.38

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	357	90	105	84	0.41	1.12	4.25	1.07	1.24
-30 (-22)	457	115	134	93	0.41	1.43	4.94	1.24	1.45
-25 (-13)	590	149	173	106	0.46	1.85	5.56	1.40	1.63
-20 (- 4)	759	191	222	123	0.55	2.38	6.15	1.55	1.80
-15 (+ 5)	964	243	282	143	0.66	3.03	6.73	1.70	1.97
-10 (+14)	1208	304	354	165	0.78	3.81	7.33	1.85	2.15

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	334	84	98	84	0.46	1.05	3.97	1.00	1.16
-30 (-22)	428	108	126	94	0.46	1.34	4.56	1.15	1.34
-25 (-13)	556	140	163	109	0.52	1.74	5.08	1.28	1.49
-20 (- 4)	717	181	210	129	0.62	2.26	5.57	1.40	1.63
-15 (+ 5)	916	231	268	152	0.73	2.88	6.04	1.52	1.77
-10 (+14)	1153	291	338	176	0.86	3.64	6.53	1.65	1.91

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper(OD)		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 42° up + 24° to Back		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 43° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		