

### COMPRESSOR DEFINITION

Designation	EM 40HNP
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513303003

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm <sup>2</sup> ] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm <sup>2</sup> ] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/10	[hp]
2 Displacement	3.77	[cm <sup>3</sup> ] (0.230 cu.in)
2.1 Bore [mm]	19.000	
2.2 Stroke [mm]	13.300	
3 Lubricant charge	160	[ml] (5.41 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	7.12	[kg] (15.70 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA17C1/8EA5B1/QPS2-A22MG1	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	4TM189NFBYY-53	
6 Start winding resistance	39.50	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	28.60	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	4.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.67	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	0.77	[A] - Measured according to UL 984
11 Approval boards certification	CE - UKCA - UL - VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
300	76	88	81	0.56	1.70	3.70	0.93	1.08

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	161	41	47	61	0.49	0.91	2.64	0.67	0.77
-30 (-22)	228	58	67	70	0.51	1.29	3.29	0.83	0.96
-25 (-13)	314	79	92	80	0.52	1.78	3.96	1.00	1.16
-20 (- 4)	420	106	123	90	0.54	2.39	4.69	1.18	1.37
-15 (+ 5)	550	138	161	100	0.57	3.14	5.48	1.38	1.61
-10 (+14)	704	177	206	110	0.62	4.03	6.37	1.61	1.87

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	108	27	32	57	0.48	0.61	1.89	0.48	0.55
-30 (-22)	179	45	52	67	0.51	1.01	2.67	0.67	0.78
-25 (-13)	267	67	78	79	0.54	1.51	3.40	0.86	1.00
-20 (- 4)	373	94	109	91	0.57	2.12	4.11	1.04	1.21
-15 (+ 5)	500	126	147	104	0.61	2.85	4.82	1.22	1.41
-10 (+14)	650	164	191	117	0.66	3.73	5.56	1.40	1.63

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	53	13	16	50	0.47	0.30	1.05	0.27	0.31
-30 (-22)	127	32	37	62	0.50	0.72	2.02	0.51	0.59
-25 (-13)	215	54	63	74	0.53	1.22	2.87	0.72	0.84
-20 (- 4)	321	81	94	89	0.57	1.83	3.63	0.91	1.06
-15 (+ 5)	445	112	131	104	0.62	2.54	4.31	1.09	1.26
-10 (+14)	592	149	173	120	0.67	3.39	4.93	1.24	1.45

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		