

COMPRESSOR DEFINITION

Designation	EM 30NR
Nominal Voltage/Frequency	220 V 60 Hz
Engineering Number	513302428

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	Blend		
3 Nominal voltage and frequency	220 / 60	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR/CSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	198 to 242 V
8.2 LBP (43°C Ambient temperature)	Static	-	198 to 242 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	14.5	[kgf/cm ²] (206 psig)	/ °C - °F
9.2 Peak (gauge)	18.2	[kgf/cm ²] (259 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/10	[hp]
2 Displacement	3.00	[cm ³] (0.183 cu.in)
2.1 Bore [mm]	19.000	
2.2 Stroke [mm]	10.600	
3 Lubricant charge	160	[ml] (5.41 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO32	
4 Weight (with oil charge)	6.73	[kg] (14.84 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	213514016	
3 Start capacitor	38-46(220)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	4TM711KFBYY-53	
6 Start winding resistance	45.50	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	29.50	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	6.80	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	0.60	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification		

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
315	79	92	89	0.60	2.31	3.54	0.89	1.04

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	158	40	46	72	0.49	1.15	2.19	0.55	0.64
-30 (-22)	225	57	66	76	0.53	1.64	2.97	0.75	0.87
-25 (-13)	309	78	90	85	0.57	2.26	3.62	0.91	1.06
-20 (- 4)	409	103	120	97	0.61	3.00	4.21	1.06	1.23
-15 (+ 5)	525	132	154	110	0.65	3.86	4.79	1.21	1.40
-10 (+14)	657	165	192	122	0.69	4.84	5.41	1.36	1.58

TEST CONDITIONS: @220V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	137	34	40	72	0.49	1.00	1.91	0.48	0.56
-30 (-22)	201	51	59	76	0.53	1.47	2.67	0.67	0.78
-25 (-13)	281	71	82	85	0.57	2.06	3.31	0.83	0.97
-20 (- 4)	379	95	111	97	0.61	2.77	3.89	0.98	1.14
-15 (+ 5)	492	124	144	110	0.65	3.61	4.47	1.13	1.31
-10 (+14)	620	156	182	122	0.69	4.57	5.10	1.28	1.49

TEST CONDITIONS: @220V60Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	90	23	26	72	0.49	0.66	1.25	0.31	0.37
-30 (-22)	150	38	44	76	0.53	1.10	2.02	0.51	0.59
-25 (-13)	227	57	67	85	0.57	1.66	2.68	0.68	0.79
-20 (- 4)	320	81	94	97	0.61	2.35	3.28	0.83	0.96
-15 (+ 5)	429	108	126	110	0.65	3.16	3.89	0.98	1.14
-10 (+14)	554	140	162	122	0.69	4.09	4.54	1.15	1.33

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		