

### COMPRESSOR DEFINITION

Designation	EM U40CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	893DA73

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low-Medium Back Pressure		
4.1 Evaporating temperature range	-35°C to -5°C	(-31°F to 23°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	7.7	[kgf/cm <sup>2</sup> ] (109 psig)	/ °C - °F
9.2 Peak (gauge)	9.8	[kgf/cm <sup>2</sup> ] (139 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	7.23	[cm <sup>3</sup> ] (0.441 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	16.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	MINERAL / ISO7	
4 Weight (with oil charge)	7.65	[kg] (16.87 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	V230	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0224/07	
6 Start winding resistance	30.42	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	28.11	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	3.50	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.62	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
414	104	121	87	0.58	1.30	4.75	1.20	1.39

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	247	62	72	60	0.50	0.77	4.12	1.04	1.21
-30	(-22)	330	83	97	68	0.52	1.03	4.85	1.22	1.42
-25	(-13)	431	109	126	76	0.53	1.35	5.65	1.42	1.66
-20	(- 4)	552	139	162	85	0.56	1.73	6.53	1.65	1.91
-15	(+ 5)	696	175	204	93	0.58	2.19	7.48	1.89	2.19
-10	(+14)	863	218	253	102	0.61	2.72	8.50	2.14	2.49
-5	(+23)	1058	267	310	110	0.65	3.35	9.58	2.42	2.81

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	230	58	67	61	0.50	0.72	3.79	0.96	1.11
-30	(-22)	311	78	91	70	0.52	0.97	4.43	1.12	1.30
-25	(-13)	409	103	120	80	0.55	1.28	5.11	1.29	1.50
-20	(- 4)	527	133	154	90	0.57	1.66	5.84	1.47	1.71
-15	(+ 5)	667	168	195	100	0.61	2.10	6.62	1.67	1.94
-10	(+14)	831	209	243	112	0.65	2.62	7.44	1.87	2.18
-5	(+23)	1021	257	299	123	0.69	3.23	8.29	2.09	2.43

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	203	51	59	61	0.50	0.64	3.36	0.85	0.98
-30	(-22)	281	71	82	72	0.52	0.88	3.93	0.99	1.15
-25	(-13)	376	95	110	83	0.55	1.18	4.53	1.14	1.33
-20	(- 4)	489	123	143	95	0.58	1.54	5.15	1.30	1.51
-15	(+ 5)	625	157	183	108	0.63	1.97	5.79	1.46	1.70
-10	(+14)	784	197	230	121	0.68	2.47	6.44	1.62	1.89
-5	(+23)	969	244	284	136	0.74	3.06	7.10	1.79	2.08

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	176	44	52	61	0.50	0.55	2.88	0.73	0.84
-30	(-22)	250	63	73	73	0.53	0.78	3.44	0.87	1.01
-25	(-13)	341	86	100	86	0.56	1.07	3.98	1.00	1.17
-20	(- 4)	450	113	132	100	0.60	1.41	4.52	1.14	1.33
-15	(+ 5)	580	146	170	115	0.66	1.83	5.06	1.27	1.48
-10	(+14)	733	185	215	132	0.72	2.31	5.58	1.40	1.63
-5	(+23)	912	230	267	150	0.80	2.89	6.08	1.53	1.78

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.95 +0.05/+0.05	[mm]	(0.195" +0.002"/+0.002")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		