

COMPRESSOR DEFINITION

Designation	EM T26CLP
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	895BA77

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	5.19	[cm ³] (0.317 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.1	[kg] (15.65 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	MI2021	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	-	[μF(VAC minimum)]
5 Motor protection	AE24AHN10	
6 Start winding resistance	26.20	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	45.70	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	2.80	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.45	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
282	71	83	66	0.47	0.89	4.26	1.07	1.25

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	128	32	38	50	0.43	0.40	2.57	0.65	0.75
-30	(-22)	202	51	59	56	0.44	0.63	3.58	0.90	1.05
-25	(-13)	276	70	81	62	0.45	0.87	4.44	1.12	1.30
-20	(- 4)	357	90	105	69	0.47	1.12	5.22	1.31	1.53
-15	(+ 5)	452	114	133	75	0.49	1.42	6.01	1.51	1.76
-10	(+14)	571	144	167	82	0.50	1.80	6.91	1.74	2.02

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	102	26	30	50	0.43	0.32	2.06	0.52	0.60
-30	(-22)	179	45	53	57	0.44	0.56	3.12	0.79	0.91
-25	(-13)	255	64	75	64	0.46	0.80	3.97	1.00	1.16
-20	(- 4)	336	85	98	71	0.48	1.06	4.71	1.19	1.38
-15	(+ 5)	431	109	126	80	0.50	1.36	5.40	1.36	1.58
-10	(+14)	548	138	160	88	0.52	1.73	6.16	1.55	1.81

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	74	19	22	49	0.43	0.23	1.52	0.38	0.44
-30	(-22)	152	38	44	57	0.45	0.48	2.61	0.66	0.76
-25	(-13)	226	57	66	66	0.47	0.71	3.44	0.87	1.01
-20	(- 4)	306	77	90	75	0.49	0.96	4.10	1.03	1.20
-15	(+ 5)	397	100	116	85	0.51	1.25	4.68	1.18	1.37
-10	(+14)	510	128	149	96	0.54	1.61	5.27	1.33	1.55

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		