

COMPRESSOR DEFINITION

Designation	EM T40CLP
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	895DA77

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	7.23	[cm ³] (0.441 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	16.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.35	[kg] (16.20 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	2019	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	-	[μF(VAC minimum)]
5 Motor protection	AE64FS	
6 Start winding resistance	26.70	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	27.20	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	4.30	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.53	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
406	102	119	93	0.68	1.27	4.38	1.10	1.28

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 35°C (+95°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	226	57	66	59	0.62	0.71	3.79	0.96	1.11
-30 (-22)	314	79	92	70	0.63	0.98	4.49	1.13	1.32
-25 (-13)	416	105	122	79	0.65	1.30	5.26	1.33	1.54
-20 (- 4)	535	135	157	88	0.67	1.68	6.12	1.54	1.79
-15 (+ 5)	676	170	198	96	0.70	2.13	7.04	1.77	2.06
-10 (+14)	841	212	246	104	0.73	2.65	8.04	2.03	2.36

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	204	51	60	59	0.62	0.64	3.44	0.87	1.01
-30 (-22)	290	73	85	72	0.64	0.91	4.05	1.02	1.19
-25 (-13)	391	98	115	83	0.66	1.23	4.72	1.19	1.38
-20 (- 4)	509	128	149	93	0.69	1.60	5.45	1.37	1.60
-15 (+ 5)	647	163	190	104	0.72	2.04	6.25	1.57	1.83
-10 (+14)	810	204	237	114	0.75	2.56	7.09	1.79	2.08

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	185	47	54	61	0.62	0.58	3.01	0.76	0.88
-30 (-22)	269	68	79	76	0.64	0.84	3.55	0.89	1.04
-25 (-13)	368	93	108	89	0.67	1.15	4.14	1.04	1.21
-20 (- 4)	483	122	142	101	0.70	1.52	4.79	1.21	1.40
-15 (+ 5)	620	156	182	113	0.74	1.95	5.48	1.38	1.60
-10 (+14)	780	197	229	125	0.78	2.46	6.21	1.56	1.82

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	163	41	48	63	0.62	0.51	2.59	0.65	0.76
-30	(-22)	246	62	72	79	0.65	0.77	3.10	0.78	0.91
-25	(-13)	342	86	100	94	0.68	1.07	3.65	0.92	1.07
-20	(- 4)	455	115	133	108	0.72	1.43	4.23	1.07	1.24
-15	(+ 5)	588	148	172	122	0.77	1.85	4.85	1.22	1.42
-10	(+14)	745	188	218	136	0.81	2.35	5.49	1.38	1.61

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		