

COMPRESSOR DEFINITION

Designation	J 7240GP
Nominal Voltage/Frequency	380-420 V 50 Hz / 440-480 V 60 Hz
Engineering Number	967CM01

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-407C		
3 Nominal voltage and frequency	380-420 / 50	[V / Hz]	
4 Application type	Air Conditioning		
4.1 Evaporating temperature range	0°C to 15°C	(32°F to 59°F)	
5 Motor type	3PHASE		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	22.4	[kgf/cm ²] (319 psig)	/ °C - °F
9.2 Peak (gauge)	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1 1/2	[hp]
2 Displacement	34.38	[cm ³] (2.098 cu.in)
2.1 Bore [mm]	42.850	
2.2 Stroke [mm]	23.850	
3 Lubricant charge	890	[ml] (30.10 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	21.4	[kg] (47.18 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	380-420 V 50 Hz / 440-480 V 60 Hz 3 ~ (Three phase)	
2 Starting device type	3PHASE	
2.1 Starting device		
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	31HM34-36	
6 Start winding resistance	4.20	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	4.20	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification		

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @440V60Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
18470	4654	5412	2174	4.10	110.24	8.50	2.14	2.49

E - PERFORMANCE - CURVES

TEST CONDITIONS: @440V50Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0 (+32)	15239	3840	4465	1341	2.63	76.86	11.37	2.86	3.33
+5 (+41)	18278	4606	5356	1410	2.73	92.85	12.96	3.27	3.80
+10 (+50)	22501	5670	6593	1475	2.87	115.30	15.25	3.84	4.47
+15 (+59)	27100	6829	7941	1534	3.03	140.26	17.67	4.45	5.18

TEST CONDITIONS: @440V50Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0 (+32)	13451	3390	3941	1483	2.87	73.17	9.07	2.29	2.66
+5 (+41)	16256	4097	4763	1590	3.04	89.26	10.21	2.57	2.99
+10 (+50)	19972	5033	5852	1688	3.21	110.56	11.84	2.98	3.47
+15 (+59)	23791	5995	6971	1775	3.40	133.15	13.41	3.38	3.93

TEST CONDITIONS: @440V50Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0 (+32)	11343	2858	3324	1626	3.11	67.28	6.98	1.76	2.04
+5 (+41)	13995	3527	4101	1769	3.35	83.80	7.90	1.99	2.31
+10 (+50)	17284	4356	5065	1900	3.56	104.30	9.12	2.30	2.67
+15 (+59)	20402	5141	5978	2017	3.76	124.84	10.10	2.54	2.96

TEST CONDITIONS: @440V60Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0 (+32)	17829	4493	5224	1569	3.08	89.92	11.37	2.86	3.33
+5 (+41)	21385	5389	6266	1650	3.20	108.64	12.96	3.27	3.80
+10 (+50)	26326	6634	7714	1726	3.35	134.90	15.25	3.84	4.47
+15 (+59)	31707	7990	9291	1795	3.55	164.11	17.67	4.45	5.18

E - PERFORMANCE - CURVES

TEST CONDITIONS: @440V60Hz		ASHRAE46 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0	(+32)	15737	3966	4611	1735	3.36	85.61	9.08	2.29	2.66
+5	(+41)	19020	4793	5573	1860	3.56	104.43	10.21	2.57	2.99
+10	(+50)	23367	5889	6847	1975	3.76	129.36	11.84	2.98	3.47
+15	(+59)	27835	7014	8156	2077	3.98	155.79	13.41	3.38	3.93

TEST CONDITIONS: @440V60Hz		ASHRAE46 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0	(+32)	13271	3344	3889	1902	3.64	78.72	6.98	1.76	2.04
+5	(+41)	16374	4126	4798	2070	3.92	98.04	7.90	1.99	2.31
+10	(+50)	20222	5096	5925	2223	4.17	122.02	9.12	2.30	2.67
+15	(+59)	23870	6015	6994	2360	4.40	146.07	10.10	2.54	2.96

F - EXTERNAL CHARACTERISTICS

1 Base plate	American Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	12.77 +0.08/+0.00	[mm]	(0.503" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	8 +0.07/+0.00	[mm]	(0.315" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted J		
3.3 PROCESS	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		