

COMPRESSOR DEFINITION

Designation	NB 6165E
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	294NA51

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-22		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	High Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	21.7	[kgf/cm ²] (309 psig)	/ °C - °F
9.2 Peak (gauge)	24.2	[kgf/cm ²] (344 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	6.05	[cm ³] (0.369 cu.in)
2.1 Bore [mm]	21.996	
2.2 Stroke [mm]	15.920	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO46	
4 Weight (with oil charge)	10.4	[kg] (22.93 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRP-0029	
3 Start capacitor	53-64(330)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0056/G5	
6 Start winding resistance	31.30	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	6.60	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	14.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	2.76	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification		

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
2642	666	774	440	2.70	16.32	6.00	1.51	1.76

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	1419	358	416	450	2.16	7.45	3.15	0.79	0.92
-10	(+14)	1742	439	510	470	2.19	9.18	3.71	0.93	1.09
-5	(+23)	2133	537	625	491	2.24	11.30	4.34	1.09	1.27
0	(+32)	2592	653	760	513	2.30	13.81	5.05	1.27	1.48
+5	(+41)	3120	786	914	536	2.39	16.73	5.82	1.47	1.71
+10	(+50)	3716	936	1089	559	2.49	20.08	6.65	1.67	1.95

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	1259	317	369	467	2.21	7.06	2.70	0.68	0.79
-10	(+14)	1550	391	454	490	2.27	8.73	3.16	0.80	0.93
-5	(+23)	1902	479	557	515	2.34	10.77	3.69	0.93	1.08
0	(+32)	2314	583	678	540	2.42	13.18	4.28	1.08	1.26
+5	(+41)	2788	703	817	566	2.52	15.99	4.92	1.24	1.44
+10	(+50)	3322	837	973	593	2.63	19.21	5.60	1.41	1.64

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	1092	275	320	484	2.26	6.59	2.26	0.57	0.66
-10	(+14)	1350	340	396	511	2.35	8.19	2.64	0.67	0.77
-5	(+23)	1661	419	487	539	2.44	10.13	3.08	0.78	0.90
0	(+32)	2025	510	593	567	2.54	12.42	3.57	0.90	1.05
+5	(+41)	2442	615	716	597	2.65	15.10	4.09	1.03	1.20
+10	(+50)	2912	734	853	628	2.77	18.16	4.64	1.17	1.36

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		