

COMPRESSOR DEFINITION

| | |
|---------------------------|------------------------|
| Designation | NB 5144Z |
| Nominal Voltage/Frequency | 208-230 V 60 Hz |
| Engineering Number | 294AD95 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|--|---|-----------------------------------|-----------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-134a | | |
| 3 Nominal voltage and frequency | 208-230 / 60 | [V / Hz] | |
| 4 Application type | High Back Pressure (Commercial Compressors) | | |
| 4.1 Evaporating temperature range | -15°C to 10°C | (5°F to 50°F) | |
| 5 Motor type | RSIR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | Operating voltage range | | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | - | - | - |
| 8.2 LBP (43°C Ambient temperature) | - | - | - |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing pressures/temperature | | | |
| 9.1 Operating (gauge) | 16.2 | [kgf/cm ²] (230 psig) | / °C - °F |
| 9.2 Peak (gauge) | 20.6 | [kgf/cm ²] (293 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|---------------|--|
| 1 Commercial designation | 1/5- | [hp] |
| 2 Displacement | 6.05 | [cm ³] (0.369 cu.in) |
| 2.1 Bore [mm] | 21.996 | |
| 2.2 Stroke [mm] | 15.920 | |
| 3 Lubricant charge | 350 | [ml] (11.84 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ESTER / ISO22 | |
| 4 Weight (with oil charge) | 10 | [kg] (22.05 lb.) |
| 5 Nitrogen charge | 0.2 to 0.3 | [kgf/cm ²] (2.84 to 4.27 psig) |

C - ELETRICAL DATA

| | | |
|--|-----------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 208-230 V 60 Hz 1~ (Single phase) | |
| 2 Starting device type | Current Relay | |
| 2.1 Starting device | MTRPH-0030 | |
| 3 Start capacitor | - | [µF(VAC minimum)] |
| 4 Run capacitor | - | [µF(VAC minimum)] |
| 5 Motor protection | T0056/G9 | |
| 6 Start winding resistance | 23.00 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 5.90 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (60 Hz) | - | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (60 Hz) | - | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (60 Hz) | - | [A] - Measured according to UL 984 |
| 11 Approval boards certification | UL | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|-------------------------------|----------|-----|--------------------------------|----------------------------------|--|---------------------------|--------------------------------------|-------|
| TEST CONDITIONS: @200V50Hz | | | ASHRAEHBP46 Static | | Evaporating temperature (Condensing temperature | | 7.2°C (44.96°F) 54.4°C (129.92°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 1840 | 464 | 539 | 312 | 2.15 | 11.93 | 5.90 | 1.49 | 1.73 |

E - PERFORMANCE - CURVES

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|------------------|------|--------------------------|
| 1 Base plate | Universal | | |
| 2 Tray holder | No | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 8.03 +0.07/+0.00 | [mm] | (0.316" +0.003"/+0.000") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Slanted 42° | | |
| 3.2 DISCHARGE | 6.45 +0.10/+0.00 | [mm] | (0.254" +0.004"/+0.000") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Straight | | |
| 3.3 PROCESS | 6.45 +0.10/+0.00 | [mm] | (0.254" +0.004"/+0.000") |
| 3.3.1 Material | Copper | | |
| 3.3.2 Shape | Slanted 42° | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |