

### COMPRESSOR DEFINITION

Designation	NE 2121Z
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	262BG70

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115 / 60	[ V / Hz ]	
4 Application type	Low Back Pressure R134a		
4.1 Evaporating temperature range	-30°C to -5°C	(-22°F to 23°F)	
5 Motor type	CSIR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm <sup>2</sup> ] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	9.26	[cm <sup>3</sup> ] (0.565 cu.in)
2.1 Bore [mm]	24.282	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	10.95	[kg] (24.14 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRPH-63	
3 Start capacitor	145-175(250)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0808/G9	
6 Start winding resistance	9.00	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.30	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	29.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	4.40	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

### D - PERFORMANCE - CHECK POINT DATA

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @100V60Hz		ASHRAE32 Fan			(Condensing temperature 35°C (+95°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	576	145	169	187	2.89	3.25	3.02	0.76	0.89
-30	(-22)	744	188	218	209	3.02	4.22	3.56	0.90	1.04
-25	(-13)	972	245	285	233	3.17	5.52	4.18	1.05	1.22
-20	(- 4)	1260	317	369	259	3.34	7.17	4.86	1.22	1.42
-15	(+ 5)	1607	405	471	288	3.54	9.18	5.58	1.41	1.63
-10	(+14)	2015	508	590	320	3.77	11.54	6.30	1.59	1.85
-5	(+23)	2482	625	727	354	4.03	14.28	7.01	1.77	2.05

TEST CONDITIONS: @100V60Hz		ASHRAE32 Fan			(Condensing temperature 45°C (+113°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	520	131	152	186	2.86	2.94	2.76	0.70	0.81
-30	(-22)	688	173	202	211	3.01	3.90	3.26	0.82	0.96
-25	(-13)	915	231	268	238	3.18	5.19	3.84	0.97	1.13
-20	(- 4)	1200	302	352	269	3.39	6.83	4.47	1.13	1.31
-15	(+ 5)	1545	389	453	301	3.62	8.82	5.13	1.29	1.50
-10	(+14)	1947	491	571	337	3.89	11.16	5.78	1.46	1.70
-5	(+23)	2409	607	706	375	4.20	13.86	6.42	1.62	1.88

TEST CONDITIONS: @100V60Hz		ASHRAE32 Fan			(Condensing temperature 55°C (+131°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	466	117	136	185	2.83	2.63	2.50	0.63	0.73
-30	(-22)	634	160	186	213	3.00	3.59	2.98	0.75	0.87
-25	(-13)	860	217	252	244	3.20	4.88	3.52	0.89	1.03
-20	(- 4)	1143	288	335	278	3.43	6.51	4.11	1.04	1.21
-15	(+ 5)	1484	374	435	314	3.70	8.47	4.73	1.19	1.38
-10	(+14)	1882	474	552	353	4.01	10.78	5.33	1.34	1.56
-5	(+23)	2338	589	685	396	4.37	13.45	5.91	1.49	1.73

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.03 +0.07/+0.00	[mm]	(0.316" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		