

### COMPRESSOR DEFINITION

Designation	NE 6195GK
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	951LG71

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	115 / 60	[ V / Hz ]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 0°C	(-4°F to 32°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	25.7	[kgf/cm <sup>2</sup> ] (365 psig)	/ °C - °F
9.2 Peak (gauge)	28.7	[kgf/cm <sup>2</sup> ] (408 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/3+	[hp]
2 Displacement	7.99	[cm <sup>3</sup> ] (0.488 cu.in)
2.1 Bore [mm]	27.775	
2.2 Stroke [mm]	13.200	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	10.4	[kg] (22.93 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELECTRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRPH-63	
3 Start capacitor	145-175(165)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0060/G9	
6 Start winding resistance	7.30	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.20	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	29.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	7.00	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
4648	1171	1362	661	7.28	38.27	7.03	1.77	2.06

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2056	518	602	384	5.34	13.05	5.35	1.35	1.57
-15	(+ 5)	2607	657	764	416	5.55	16.64	6.27	1.58	1.84
-10	(+14)	3279	826	961	447	5.76	21.06	7.34	1.85	2.15
-5	(+23)	4071	1026	1193	478	5.98	26.34	8.51	2.15	2.49
0	(+32)	4984	1256	1460	509	6.19	32.53	9.79	2.47	2.87
+5	(+41)	6019	1517	1764	541	6.40	39.68	11.15	2.81	3.27
+10	(+50)	7175	1808	2103	574	6.61	47.82	12.58	3.17	3.69

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1645	414	482	369	5.25	11.52	4.46	1.12	1.31
-15	(+ 5)	2152	542	631	416	5.55	15.17	5.17	1.30	1.52
-10	(+14)	2758	695	808	461	5.85	19.58	5.98	1.51	1.75
-5	(+23)	3463	873	1015	505	6.15	24.78	6.86	1.73	2.01
0	(+32)	4267	1075	1250	548	6.45	30.82	7.79	1.96	2.28
+5	(+41)	5170	1303	1515	590	6.75	37.74	8.76	2.21	2.57
+10	(+50)	6172	1555	1809	633	7.04	45.57	9.75	2.46	2.86

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1216	307	356	353	5.16	9.57	3.45	0.87	1.01
-15	(+ 5)	1678	423	492	416	5.55	13.28	4.03	1.02	1.18
-10	(+14)	2215	558	649	476	5.94	17.67	4.66	1.17	1.36
-5	(+23)	2829	713	829	533	6.33	22.78	5.31	1.34	1.56
0	(+32)	3520	887	1031	588	6.72	28.66	5.98	1.51	1.75
+5	(+41)	4288	1081	1257	641	7.10	35.33	6.64	1.67	1.95
+10	(+50)	5134	1294	1504	694	7.48	42.86	7.28	1.83	2.13

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.03 +0.07/+0.00	[mm]	(0.316" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		