

COMPRESSOR DEFINITION

Designation	NE 2130Z
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	262DG70

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115 / 60	[V / Hz]	
4 Application type	Low Back Pressure R134a		
4.1 Evaporating temperature range	-30°C to -5°C	(-22°F to 23°F)	
5 Motor type	CSIR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	12.11	[cm ³] (0.739 cu.in)
2.1 Bore [mm]	27.775	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	10.95	[kg] (24.14 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	9660A-XX-189	
3 Start capacitor	145-175(250)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0748/G9	
6 Start winding resistance	9.15	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.20	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	38.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	4.90	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

E - PERFORMANCE - CURVES

TEST CONDITIONS: @100V60Hz		ASHRAE32 Fan			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	817	206	239	205	4.74	4.62	3.86	0.97	1.13
-30	(-22)	997	251	292	239	4.76	5.65	4.16	1.05	1.22
-25	(-13)	1260	317	369	276	4.83	7.15	4.58	1.15	1.34
-20	(- 4)	1606	405	471	316	4.96	9.14	5.09	1.28	1.49
-15	(+ 5)	2035	513	596	358	5.14	11.62	5.68	1.43	1.66
-10	(+14)	2548	642	747	403	5.37	14.60	6.32	1.59	1.85
-5	(+23)	3143	792	921	450	5.65	18.08	6.99	1.76	2.05

TEST CONDITIONS: @100V60Hz		ASHRAE32 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	702	177	206	210	4.68	3.96	3.30	0.83	0.97
-30	(-22)	912	230	267	246	4.73	5.17	3.71	0.93	1.09
-25	(-13)	1196	301	350	285	4.84	6.79	4.19	1.06	1.23
-20	(- 4)	1552	391	455	328	5.00	8.83	4.73	1.19	1.39
-15	(+ 5)	1981	499	580	373	5.21	11.31	5.31	1.34	1.56
-10	(+14)	2482	625	727	421	5.47	14.22	5.89	1.49	1.73
-5	(+23)	3055	770	895	472	5.78	17.58	6.47	1.63	1.90

TEST CONDITIONS: @100V60Hz		ASHRAE32 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	588	148	172	215	4.62	3.32	2.76	0.70	0.81
-30	(-22)	830	209	243	253	4.71	4.70	3.29	0.83	0.96
-25	(-13)	1134	286	332	294	4.85	6.44	3.85	0.97	1.13
-20	(- 4)	1500	378	440	339	5.04	8.54	4.42	1.11	1.30
-15	(+ 5)	1928	486	565	387	5.28	11.01	4.99	1.26	1.46
-10	(+14)	2419	610	709	439	5.57	13.86	5.52	1.39	1.62
-5	(+23)	2971	749	871	493	5.91	17.09	6.02	1.52	1.76

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.03 +0.07/+0.00	[mm]	(0.316" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		