

COMPRESSOR DEFINITION

Designation	NE K6212Z
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	269AG71

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115 / 60	[V / Hz]	
4 Application type	High Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/2	[hp]
2 Displacement	14.28	[cm ³] (0.871 cu.in)
2.1 Bore [mm]	30.157	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.6	[kg] (25.57 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	9660A-XX-189	
3 Start capacitor	189-227(250)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0625/G8	
6 Start winding resistance	0.86	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	5.50	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

E - PERFORMANCE - CURVES

TEST CONDITIONS: @100V60Hz		ASHRAE46 Fan			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	2564	646	751	431	6.99	13.87	5.94	1.50	1.74
-10	(+14)	3256	820	954	468	7.14	17.67	6.95	1.75	2.04
-5	(+23)	4055	1022	1188	515	7.37	22.09	7.86	1.98	2.30
0	(+32)	4965	1251	1455	574	7.70	27.16	8.66	2.18	2.54
+5	(+41)	5986	1509	1754	643	8.12	32.93	9.31	2.35	2.73
+10	(+50)	7122	1795	2087	725	8.63	39.44	9.82	2.48	2.88

TEST CONDITIONS: @100V60Hz		ASHRAE46 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	2224	560	652	449	7.04	13.00	4.95	1.25	1.45
-10	(+14)	2858	720	837	497	7.27	16.76	5.76	1.45	1.69
-5	(+23)	3599	907	1055	552	7.57	21.19	6.53	1.65	1.91
0	(+32)	4449	1121	1304	613	7.93	26.32	7.26	1.83	2.13
+5	(+41)	5409	1363	1585	683	8.36	32.19	7.92	2.00	2.32
+10	(+50)	6483	1634	1900	760	8.87	38.86	8.51	2.14	2.49

TEST CONDITIONS: @100V60Hz		ASHRAE46 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	1936	488	567	464	7.09	12.33	4.17	1.05	1.22
-10	(+14)	2481	625	727	527	7.43	15.87	4.71	1.19	1.38
-5	(+23)	3132	789	918	592	7.81	20.13	5.29	1.33	1.55
0	(+32)	3891	981	1140	660	8.24	25.14	5.89	1.48	1.73
+5	(+41)	4760	1200	1395	732	8.71	30.95	6.50	1.64	1.91
+10	(+50)	5741	1447	1682	808	9.23	37.59	7.11	1.79	2.08

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		