

COMPRESSOR DEFINITION

Designation	NE K2150GK
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	959AG71

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	115 / 60	[V / Hz]	
4 Application type	Low Back Pressure R404A		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	25.7	[kgf/cm ²] (365 psig)	/ °C - °F
9.2 Peak (gauge)	28.7	[kgf/cm ²] (408 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/2+	[hp]
2 Displacement	12.11	[cm ³] (0.739 cu.in)
2.1 Bore [mm]	27.775	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.6	[kg] (25.57 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	9660A-XX-189	
3 Start capacitor	189-227(165)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0873/G9	
6 Start winding resistance	4.50	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	0.77	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

E - PERFORMANCE - CURVES

TEST CONDITIONS: @100V60Hz		ASHRAE32 Fan			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1239	312	363	342	5.79	8.33	3.61	0.91	1.06
-35	(-31)	1576	397	462	395	6.13	10.63	4.00	1.01	1.17
-30	(-22)	2017	508	591	451	6.48	13.64	4.48	1.13	1.31
-25	(-13)	2561	645	750	508	6.85	17.40	5.03	1.27	1.47
-20	(- 4)	3208	808	940	569	7.24	21.91	5.63	1.42	1.65
-15	(+ 5)	3959	998	1160	633	7.66	27.20	6.26	1.58	1.83
-10	(+14)	4814	1213	1411	700	8.10	33.30	6.88	1.73	2.02

TEST CONDITIONS: @100V60Hz		ASHRAE32 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1113	280	326	345	5.86	7.47	3.22	0.81	0.94
-35	(-31)	1449	365	425	406	6.21	9.75	3.58	0.90	1.05
-30	(-22)	1883	474	552	470	6.59	12.71	4.01	1.01	1.17
-25	(-13)	2413	608	707	536	7.01	16.36	4.49	1.13	1.32
-20	(- 4)	3040	766	891	606	7.46	20.72	5.01	1.26	1.47
-15	(+ 5)	3764	949	1103	680	7.96	25.81	5.54	1.40	1.62
-10	(+14)	4585	1155	1344	758	8.50	31.66	6.05	1.52	1.77

TEST CONDITIONS: @100V60Hz		ASHRAE32 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	974	245	285	344	5.91	6.52	2.83	0.71	0.83
-35	(-31)	1309	330	384	413	6.28	8.80	3.17	0.80	0.93
-30	(-22)	1735	437	508	485	6.70	11.69	3.57	0.90	1.05
-25	(-13)	2252	567	660	561	7.17	15.24	4.01	1.01	1.17
-20	(- 4)	2858	720	838	641	7.70	19.44	4.46	1.12	1.31
-15	(+ 5)	3556	896	1042	725	8.28	24.33	4.91	1.24	1.44
-10	(+14)	4344	1095	1273	814	8.93	29.93	5.33	1.34	1.56

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		