

COMPRESSOR DEFINITION

Designation	NJ 6220Z
Nominal Voltage/Frequency	208-230 V 60 Hz
Engineering Number	144HD01

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	208-230 / 60	[V / Hz]	
4 Application type	High Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1	[hp]
2 Displacement	26.11	[cm ³] (1.593 cu.in)
2.1 Bore [mm]	41.770	
2.2 Stroke [mm]	19.066	
3 Lubricant charge	750	[ml] (25.36 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	20.25	[kg] (44.64 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	208-230 V 60 Hz 1~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	3ARR2KCP78S	
3 Start capacitor	88-108(330)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0820/20	
6 Start winding resistance	8.09	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.45	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	42.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

E - PERFORMANCE - CURVES

TEST CONDITIONS:		ASHRAE46			(Condensing temperature 35°C (+95°F))					
@200V60Hz		Fan								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-15 (+ 5)	4190	1056	1228	634	5.50	22.64	6.60	1.66	1.93	
-10 (+14)	5630	1419	1650	725	5.77	30.56	7.76	1.96	2.28	
-5 (+23)	7260	1830	2127	816	6.06	39.56	8.91	2.25	2.61	
0 (+32)	9081	2288	2661	906	6.37	49.70	10.04	2.53	2.94	
+5 (+41)	11093	2795	3251	995	6.69	61.03	11.15	2.81	3.27	
+10 (+50)	13296	3351	3896	1084	7.03	73.60	12.24	3.09	3.59	

TEST CONDITIONS:		ASHRAE46			(Condensing temperature 45°C (+113°F))					
@200V60Hz		Fan								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-15 (+ 5)	3273	825	959	629	5.48	19.14	5.21	1.31	1.53	
-10 (+14)	4557	1148	1335	740	5.82	26.72	6.14	1.55	1.80	
-5 (+23)	6048	1524	1772	853	6.18	35.59	7.08	1.78	2.07	
0 (+32)	7748	1953	2270	966	6.58	45.83	8.02	2.02	2.35	
+5 (+41)	9657	2434	2830	1079	7.00	57.47	8.96	2.26	2.62	
+10 (+50)	11774	2967	3450	1192	7.46	70.57	9.90	2.49	2.90	

TEST CONDITIONS:		ASHRAE46			(Condensing temperature 55°C (+131°F))					
@200V60Hz		Fan								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-15 (+ 5)	2545	641	746	608	5.41	16.22	4.19	1.05	1.23	
-10 (+14)	3599	907	1055	739	5.80	23.02	4.88	1.23	1.43	
-5 (+23)	4879	1229	1430	871	6.23	31.34	5.60	1.41	1.64	
0 (+32)	6384	1609	1871	1005	6.71	41.24	6.35	1.60	1.86	
+5 (+41)	8116	2045	2378	1141	7.24	52.77	7.11	1.79	2.08	
+10 (+50)	10074	2539	2952	1277	7.81	65.98	7.89	1.99	2.31	

F - EXTERNAL CHARACTERISTICS

1 Base plate	American Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	8 +0.07/+0.00	[mm]	(0.315" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted J		
3.3 PROCESS	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		