

### COMPRESSOR DEFINITION

|                           |                 |
|---------------------------|-----------------|
| Designation               | VEG Y6H         |
| Nominal Voltage/Frequency | 230 V 53-150 Hz |
| Engineering Number        | 513800055       |

### A - APPLICATION / LIMIT WORKING CONDITIONS

|  |                                   |                                   |           |
|--|-----------------------------------|-----------------------------------|-----------|
| 1 Type                                     | Hermetic reciprocating compressor |                                   |           |
| 2 Refrigerant                              | R-134a                            |                                   |           |
| 3 Nominal voltage and frequency            | 230 / 53-150                      | [ V / Hz ]                        |           |
| 4 Application type                         | Low Back Pressure                 |                                   |           |
| 4.1 Evaporating temperature range          | -35°C to -10°C                    | (-31°F to 14°F)                   |           |
| 5 Motor type                               | BPM                               |                                   |           |
| 6 Starting torque                          | LST - Low Starting Torque         |                                   |           |
| 7 Expansion device                         | Capillary tube                    |                                   |           |
| 8 Compressor cooling                       | Operating voltage range           |                                   |           |
|  |                                   | 50 Hz                             | 60 Hz     |
| 8.1 LBP (32°C Ambient temperature)         | -                                 | -                                 | -         |
| 8.2 LBP (43°C Ambient temperature)         | -                                 | -                                 | -         |
| 8.3 HBP (32°C Ambient temperature)         | -                                 | -                                 | -         |
| 8.4 HBP (43°C Ambient temperature)         | -                                 | -                                 | -         |
| 9 Maximum condensing pressures/temperature |                                   |                                   |           |
| 9.1 Operating (gauge)                      | 16.2                              | [kgf/cm <sup>2</sup> ] (230 psig) | / °C - °F |
| 9.2 Peak (gauge)                           | 20.6                              | [kgf/cm <sup>2</sup> ] (293 psig) | / °C - °F |
| 10 Maximum winding temperature             | 130                               | [ °C ]                            |           |

### B - MECHANICAL DATA

|                               |               |  |
|-------------------------------|---------------|--|
| 1 Commercial designation      | 1/5           | [hp]                                       |
| 2 Displacement                | 6.36          | [cm <sup>3</sup> ] (0.388 cu.in)           |
| 2.1 Bore [mm]                 | 22.500        |  |
| 2.2 Stroke [mm]               | 16.000        |  |
| 3 Lubricant charge            | 430           | [ml] (14.54 fl.oz.)                        |
| 3.1 Lubricants approved       |               |  |
| 3.2 Lubricants type/viscosity | ESTER / ISO10 |  |
| 4 Weight (with oil charge)    | 10.9          | [kg] (24.03 lb.)                           |
| 5 Nitrogen charge             | 0.2 to 0.3    | [kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig) |

### C - ELETRICAL DATA

|  |                                   |                                    |
|--|-----------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 230 V 53-150 Hz 3 ~ (Three phase) |                                    |
| 2 Starting device type                       | Inverter                          |                                    |
| 2.1 Starting device                          | VCC32456XXXX                      |                                    |
| 3 Start capacitor                            | -                                 | [µF(VAC minimum)]                  |
| 4 Run capacitor                              | -                                 | [µF(VAC minimum)]                  |
| 5 Motor protection                           | VCC32456XXXXX                     |                                    |
| 6 Start winding resistance                   | 6.40                              | [Ω at 25°C (77°F)] +/- 8%          |
| 7 Run winding resistance                     | 6.40                              | [Ω at 25°C (77°F)] +/- 8%          |
| 8 LRA - Locked rotor amperage (50/60 Hz)     | 3.30                              | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50/60 Hz)  | 3.30                              | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (50/60 Hz)   | -                                 | [A] - Measured according to UL 984 |
| 11 Approval boards certification             |                                   |                                    |

**D - PERFORMANCE - CHECK POINT DATA**

---

**E - PERFORMANCE - CURVES**

---

### F - EXTERNAL CHARACTERISTICS

|                         |                               |      |                          |
|-------------------------|-------------------------------|------|--------------------------|
| 1 Base plate            | Universal EG/F/AMEM version 2 |      |                          |
| 2 Tray holder           | No                            |      |                          |
| 3 Connectors            |                               |      |                          |
| 3.1 SUCTION             | 8.2 +0.12/-0.08               | [mm] | (0.323" +0.005"/-0.003") |
| 3.1.1 Material          | Copper                        |      |                          |
| 3.1.2 Shape             | Straight                      |      |                          |
| 3.2 DISCHARGE           | 6.5 +0.12/-0.08               | [mm] | (0.256" +0.005"/-0.003") |
| 3.2.1 Material          | Copper                        |      |                          |
| 3.2.2 Shape             | Straight                      |      |                          |
| 3.3 PROCESS             | 6.5 +0.12/-0.08               | [mm] | (0.256" +0.005"/-0.003") |
| 3.3.1 Material          | Copper                        |      |                          |
| 3.3.2 Shape             | Straight                      |      |                          |
| 3.4 Oil cooler (Copper) | No                            | [mm] |                          |
| 3.5 Connector sealing   | Rubber Plugs                  |      |                          |