

COMPRESSOR DEFINITION

Designation	EM X32CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	898CA89

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	5.96	[cm ³] (0.364 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	8	[kg] (17.64 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	MI2021	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	2.5(440)	[μF(VAC minimum)]
5 Motor protection	AE23AHNX	
6 Start winding resistance	34.75	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	37.70	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	2.60	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.23	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	IRAM - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
330	83	97	59	0.27	1.04	5.57	1.40	1.63

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	177	45	52	40	0.19	0.55	4.38	1.10	1.28
-30	(-22)	242	61	71	47	0.22	0.76	5.12	1.29	1.50
-25	(-13)	319	80	93	54	0.25	1.00	5.90	1.49	1.73
-20	(- 4)	412	104	121	61	0.28	1.29	6.76	1.70	1.98
-15	(+ 5)	527	133	154	68	0.31	1.66	7.75	1.95	2.27
-10	(+14)	666	168	195	74	0.34	2.10	8.92	2.25	2.61

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	148	37	43	39	0.19	0.46	3.77	0.95	1.10
-30	(-22)	219	55	64	48	0.22	0.69	4.55	1.15	1.33
-25	(-13)	299	75	88	57	0.26	0.94	5.29	1.33	1.55
-20	(- 4)	393	99	115	65	0.29	1.23	6.03	1.52	1.77
-15	(+ 5)	503	127	148	74	0.33	1.59	6.81	1.72	2.00
-10	(+14)	636	160	186	82	0.37	2.01	7.69	1.94	2.25

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	123	31	36	38	0.19	0.38	3.20	0.81	0.94
-30	(-22)	200	50	59	48	0.23	0.63	4.08	1.03	1.20
-25	(-13)	282	71	83	58	0.27	0.89	4.84	1.22	1.42
-20	(- 4)	374	94	110	68	0.31	1.18	5.51	1.39	1.61
-15	(+ 5)	481	121	141	79	0.36	1.51	6.15	1.55	1.80
-10	(+14)	606	153	178	89	0.41	1.91	6.81	1.72	2.00

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 42°		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		