

COMPRESSOR DEFINITION

| | |
|---------------------------|------------------------|
| Designation | EM X40CLC |
| Nominal Voltage/Frequency | 220-240 V 50 Hz |
| Engineering Number | 898DA77 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|------------------------------------|-----------------------------------|-----------------------------------|-----------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-600a | | |
| 3 Nominal voltage and frequency | 220-240 / 50 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSCR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | | Operating voltage range | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | 198 to 254 V | - |
| 8.2 LBP (43°C Ambient temperature) | Static | 198 to 254 V | - |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing temperature | | | |
| 9.1 Operating | 6.9 | [kgf/cm ²] (98 psig) | / °C - °F |
| 9.2 Peak | 7.8 | [kgf/cm ²] (111 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|----------------|----------------------------------|
| 1 Commercial designation | | [hp] |
| 2 Displacement | 7.23 | [cm ³] (0.441 cu.in) |
| 2.1 Bore [mm] | 24.000 | |
| 2.2 Stroke [mm] | 16.000 | |
| 3 Lubricant charge | 180 | [ml] (6.09 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ALQUILB / ISO5 | |
| 4 Weight (with oil charge) | 7.8 | [kg] (17.20 lb.) |
| 5 Nitrogen charge | - | [kgf/cm ²] |

C - ELETRICAL DATA

| | | |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50 Hz 1 ~ (Single phase) | |
| 2 Starting device type | PTC | |
| 2.1 Starting device | V230 | |
| 3 Start capacitor | - | [μF(VAC minimum)] |
| 4 Run capacitor | 4(440) | [μF(VAC minimum)] |
| 5 Motor protection | T0224/07 | |
| 6 Start winding resistance | 22.40 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 28.80 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (50 Hz) | 3.10 | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50 Hz) | 0.30 | [A] |
| 10 FLA - Full Load Amperage HBP (50 Hz) | - | [A] |
| 11 Approval boards certification | IRAM - VDE | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|-------------------------------|----------|-----|-----------------------------|-------------------------------|--|---------------------------|--|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 412 | 104 | 121 | 73 | 0.33 | 1.29 | 5.63 | 1.42 | 1.65 |

E - PERFORMANCE - CURVES

| | | | | | | | | | | |
|-------------------------------|-------|----------------------------|--------------------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 45°C (+113°F)) | | | | | |
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 27 | 7 | 8 | 48 | 0.23 | 0.09 | 0.56 | 0.14 | 0.17 |
| -30 | (-22) | 37 | 9 | 11 | 58 | 0.27 | 0.12 | 0.64 | 0.16 | 0.19 |
| -25 | (-13) | 49 | 12 | 14 | 67 | 0.31 | 0.15 | 0.74 | 0.19 | 0.22 |
| -20 | (- 4) | 63 | 16 | 18 | 75 | 0.35 | 0.20 | 0.84 | 0.21 | 0.25 |
| -15 | (+ 5) | 80 | 20 | 23 | 83 | 0.39 | 0.25 | 0.96 | 0.24 | 0.28 |
| -10 | (+14) | 100 | 25 | 29 | 92 | 0.43 | 0.32 | 1.08 | 0.27 | 0.32 |

| | | | | | | | | | | |
|-------------------------------|-------|----------------------------|--------------------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 55°C (+131°F)) | | | | | |
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 21 | 5 | 6 | 49 | 0.23 | 0.07 | 0.43 | 0.11 | 0.13 |
| -30 | (-22) | 30 | 8 | 9 | 60 | 0.27 | 0.10 | 0.50 | 0.13 | 0.15 |
| -25 | (-13) | 41 | 10 | 12 | 70 | 0.32 | 0.13 | 0.59 | 0.15 | 0.17 |
| -20 | (- 4) | 54 | 14 | 16 | 80 | 0.36 | 0.17 | 0.67 | 0.17 | 0.20 |
| -15 | (+ 5) | 69 | 17 | 20 | 90 | 0.41 | 0.22 | 0.77 | 0.19 | 0.23 |
| -10 | (+14) | 87 | 22 | 26 | 101 | 0.46 | 0.28 | 0.87 | 0.22 | 0.25 |

| | | | | | | | | | | |
|-------------------------------|-------|----------------------------|--------------------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 65°C (+149°F)) | | | | | |
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 16 | 4 | 5 | 48 | 0.23 | 0.05 | 0.33 | 0.08 | 0.10 |
| -30 | (-22) | 24 | 6 | 7 | 60 | 0.28 | 0.08 | 0.40 | 0.10 | 0.12 |
| -25 | (-13) | 34 | 9 | 10 | 71 | 0.33 | 0.11 | 0.47 | 0.12 | 0.14 |
| -20 | (- 4) | 45 | 11 | 13 | 82 | 0.38 | 0.14 | 0.55 | 0.14 | 0.16 |
| -15 | (+ 5) | 58 | 15 | 17 | 94 | 0.44 | 0.18 | 0.62 | 0.16 | 0.18 |
| -10 | (+14) | 74 | 19 | 22 | 107 | 0.50 | 0.23 | 0.69 | 0.18 | 0.20 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|-------------------|------|--------------------------|
| 1 Base plate | European Standard | | |
| 2 Tray holder | Yes | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Slanted 42° | | |
| 3.2 DISCHARGE | 4.94 +0.08/-0.08 | [mm] | (0.194" +0.003"/-0.003") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Straight | | |
| 3.3 PROCESS | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.3.1 Material | Copper | | |
| 3.3.2 Shape | Slanted 42° | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |