

### COMPRESSOR DEFINITION

|                           |                 |
|---------------------------|-----------------|
| Designation               | EM X20CLC       |
| Nominal Voltage/Frequency | 220-240 V 50 Hz |
| Engineering Number        | 898AA88         |

### A - APPLICATION / LIMIT WORKING CONDITIONS

|                                    |                                   |                                   |           |
|------------------------------------|-----------------------------------|-----------------------------------|-----------|
| 1 Type                             | Hermetic reciprocating compressor |                                   |           |
| 2 Refrigerant                      | R-600a                            |                                   |           |
| 3 Nominal voltage and frequency    | 220-240 / 50                      | [ V / Hz ]                        |           |
| 4 Application type                 | Low Back Pressure                 |                                   |           |
| 4.1 Evaporating temperature range  | -35°C to -10°C                    | (-31°F to 14°F)                   |           |
| 5 Motor type                       | RSCR                              |                                   |           |
| 6 Starting torque                  | LST - Low Starting Torque         |                                   |           |
| 7 Expansion device                 | Capillary tube                    |                                   |           |
| 8 Compressor cooling               |                                   | Operating voltage range           |           |
|                                    |                                   | 50 Hz                             | 60 Hz     |
| 8.1 LBP (32°C Ambient temperature) | Static                            | 198 to 254 V                      | -         |
| 8.2 LBP (43°C Ambient temperature) | Static                            | 198 to 254 V                      | -         |
| 8.3 HBP (32°C Ambient temperature) | -                                 | -                                 | -         |
| 8.4 HBP (43°C Ambient temperature) | -                                 | -                                 | -         |
| 9 Maximum condensing temperature   |                                   |                                   |           |
| 9.1 Operating                      | 6.9                               | [kgf/cm <sup>2</sup> ] (98 psig)  | / °C - °F |
| 9.2 Peak                           | 7.8                               | [kgf/cm <sup>2</sup> ] (111 psig) | / °C - °F |
| 10 Maximum winding temperature     | 130                               | [ °C ]                            |           |

### B - MECHANICAL DATA

|                               |                |                                  |
|-------------------------------|----------------|----------------------------------|
| 1 Commercial designation      |                | [hp]                             |
| 2 Displacement                | 3.97           | [cm <sup>3</sup> ] (0.242 cu.in) |
| 2.1 Bore [mm]                 | 19.000         |                                  |
| 2.2 Stroke [mm]               | 14.000         |                                  |
| 3 Lubricant charge            | 180            | [ml] (6.09 fl.oz.)               |
| 3.1 Lubricants approved       |                |                                  |
| 3.2 Lubricants type/viscosity | ALQUILB / ISO5 |                                  |
| 4 Weight (with oil charge)    | 7.8            | [kg] (17.20 lb.)                 |
| 5 Nitrogen charge             | -              | [kgf/cm <sup>2</sup> ]           |

### C - ELETRICAL DATA

|  |                                    |                                    |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50 Hz 1 ~ (Single phase) |                                    |
| 2 Starting device type                       | TSD                                |                                    |
| 2.1 Starting device                          | MI.E-START 2021                    |                                    |
| 3 Start capacitor                            | -                                  | [μF(VAC minimum)]                  |
| 4 Run capacitor                              | 2(440)                             | [μF(VAC minimum)]                  |
| 5 Motor protection                           | AE23AHNX                           |                                    |
| 6 Start winding resistance                   | 34.90                              | [Ω at 25°C (77°F)] +/- 8%          |
| 7 Run winding resistance                     | 47.80                              | [Ω at 25°C (77°F)] +/- 8%          |
| 8 LRA - Locked rotor amperage (50 Hz)        | 2.00                               | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50 Hz)     | 0.18                               | [A]                                |
| 10 FLA - Full Load Amperage HBP (50 Hz)      | -                                  | [A]                                |
| 11 Approval boards certification             | IRAM - VDE                         |                                    |

### D - PERFORMANCE - CHECK POINT DATA

|                               |          |     |                             |                               |  |                           |  |       |
|-------------------------------|----------|-----|-----------------------------|-------------------------------|--|---------------------------|--|-------|
| TEST CONDITIONS:<br>@220V50Hz |          |     | ASHRAELBP32<br>Static       |                               | Evaporating temperature<br>(Condensing temperature |                           | -23.3°C (-9.94°F)<br>54.4°C (129.92°F) |       |
| Cooling capacity<br>+/- 5%    |          |     | Power consumption<br>+/- 5% | Current consumption<br>+/- 5% | Gas flow rate<br>+/- 5%                            | EFFICIENCY RATE<br>+/- 7% |  |       |
| [Btu/h]                       | [kcal/h] | [W] | [W]                         | [A]                           | [kg/h]   | [Btu/Wh]                  | [kcal/Wh]                              | [W/W] |
| 208                           | 52       | 61  | 39                          | 0.18                          | 0.65   | 5.36                      | 1.35                                   | 1.57  |

### E - PERFORMANCE - CURVES

|                               |       |                            |                    |     |  |                               |                         |                           |           |       |
|-------------------------------|-------|----------------------------|--------------------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS:<br>@220V50Hz |       |                            | ASHRAE32<br>Static |     | (Condensing temperature 45°C (+113°F)) |                               |                         |                           |           |       |
| Evaporating temperature       |       | Cooling capacity<br>+/- 5% |                    |     | Power consumption<br>+/- 5%            | Current consumption<br>+/- 5% | Gas flow rate<br>+/- 5% | EFFICIENCY RATE<br>+/- 7% |           |       |
| °C                            | (°F)  | [Btu/h]                    | [kcal/h]           | [W] | [W]                                    | [A]                           | [kg/h]                  | [Btu/Wh]                  | [kcal/Wh] | [W/W] |
| -35                           | (-31) | 108                        | 27                 | 32  | 28                                     | 0.13                          | 0.34                    | 3.95                      | 0.99      | 1.16  |
| -30                           | (-22) | 155                        | 39                 | 45  | 32                                     | 0.15                          | 0.49                    | 4.89                      | 1.23      | 1.43  |
| -25                           | (-13) | 210                        | 53                 | 61  | 36                                     | 0.16                          | 0.66                    | 5.83                      | 1.47      | 1.71  |
| -20                           | (- 4) | 274                        | 69                 | 80  | 40                                     | 0.18                          | 0.86                    | 6.81                      | 1.72      | 2.00  |
| -15                           | (+ 5) | 350                        | 88                 | 102 | 45                                     | 0.21                          | 1.10                    | 7.86                      | 1.98      | 2.30  |
| -10                           | (+14) | 439                        | 111                | 129 | 49                                     | 0.22                          | 1.38                    | 9.02                      | 2.27      | 2.64  |

|                               |       |                            |                    |     |  |                               |                         |                           |           |       |
|-------------------------------|-------|----------------------------|--------------------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS:<br>@220V50Hz |       |                            | ASHRAE32<br>Static |     | (Condensing temperature 55°C (+131°F)) |                               |                         |                           |           |       |
| Evaporating temperature       |       | Cooling capacity<br>+/- 5% |                    |     | Power consumption<br>+/- 5%            | Current consumption<br>+/- 5% | Gas flow rate<br>+/- 5% | EFFICIENCY RATE<br>+/- 7% |           |       |
| °C                            | (°F)  | [Btu/h]                    | [kcal/h]           | [W] | [W]                                    | [A]                           | [kg/h]                  | [Btu/Wh]                  | [kcal/Wh] | [W/W] |
| -35                           | (-31) | 92                         | 23                 | 27  | 28                                     | 0.13                          | 0.29                    | 3.31                      | 0.83      | 0.97  |
| -30                           | (-22) | 135                        | 34                 | 40  | 32                                     | 0.15                          | 0.42                    | 4.19                      | 1.05      | 1.23  |
| -25                           | (-13) | 187                        | 47                 | 55  | 37                                     | 0.17                          | 0.59                    | 5.03                      | 1.27      | 1.47  |
| -20                           | (- 4) | 249                        | 63                 | 73  | 42                                     | 0.19                          | 0.78                    | 5.88                      | 1.48      | 1.72  |
| -15                           | (+ 5) | 322                        | 81                 | 94  | 48                                     | 0.22                          | 1.01                    | 6.76                      | 1.70      | 1.98  |
| -10                           | (+14) | 410                        | 103                | 120 | 53                                     | 0.25                          | 1.29                    | 7.73                      | 1.95      | 2.26  |

|                               |       |                            |                    |     |  |                               |                         |                           |           |       |
|-------------------------------|-------|----------------------------|--------------------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS:<br>@220V50Hz |       |                            | ASHRAE32<br>Static |     | (Condensing temperature 65°C (+149°F)) |                               |                         |                           |           |       |
| Evaporating temperature       |       | Cooling capacity<br>+/- 5% |                    |     | Power consumption<br>+/- 5%            | Current consumption<br>+/- 5% | Gas flow rate<br>+/- 5% | EFFICIENCY RATE<br>+/- 7% |           |       |
| °C                            | (°F)  | [Btu/h]                    | [kcal/h]           | [W] | [W]                                    | [A]                           | [kg/h]                  | [Btu/Wh]                  | [kcal/Wh] | [W/W] |
| -35                           | (-31) | 75                         | 19                 | 22  | 27                                     | 0.13                          | 0.24                    | 2.74                      | 0.69      | 0.80  |
| -30                           | (-22) | 116                        | 29                 | 34  | 32                                     | 0.15                          | 0.36                    | 3.60                      | 0.91      | 1.05  |
| -25                           | (-13) | 165                        | 42                 | 48  | 38                                     | 0.18                          | 0.52                    | 4.38                      | 1.10      | 1.28  |
| -20                           | (- 4) | 225                        | 57                 | 66  | 44                                     | 0.20                          | 0.71                    | 5.13                      | 1.29      | 1.50  |
| -15                           | (+ 5) | 298                        | 75                 | 87  | 51                                     | 0.23                          | 0.94                    | 5.89                      | 1.48      | 1.73  |
| -10                           | (+14) | 385                        | 97                 | 113 | 57                                     | 0.27                          | 1.21                    | 6.69                      | 1.69      | 1.96  |

### F - EXTERNAL CHARACTERISTICS

|                         |                   |      |                          |
|-------------------------|-------------------|------|--------------------------|
| 1 Base plate            | European Standard |      |                          |
| 2 Tray holder           | Yes               |      |                          |
| 3 Connectors            |                   |      |                          |
| 3.1 SUCTION             | 6.1 +0.10/+0.00   | [mm] | (0.240" +0.004"/+0.000") |
| 3.1.1 Material          | Copper            |      |                          |
| 3.1.2 Shape             | Slanted 42°       |      |                          |
| 3.2 DISCHARGE           | 5.1 +0.10/+0.00   | [mm] | (0.201" +0.004"/+0.000") |
| 3.2.1 Material          | Copper            |      |                          |
| 3.2.2 Shape             | Slanted 42°       |      |                          |
| 3.3 PROCESS             | 6 +0.08/-0.08     | [mm] | (0.236" +0.003"/-0.003") |
| 3.3.1 Material          | Copper(OD)        |      |                          |
| 3.3.2 Shape             | Slanted 42°       |      |                          |
| 3.4 Oil cooler (Copper) | No                | [mm] |                          |
| 3.5 Connector sealing   | Rubber Plugs      |      |                          |