

COMPRESSOR DEFINITION

Designation	EM Y40CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	897DA96

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR-RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	7.23	[cm ³] (0.441 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	16.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.65	[kg] (16.87 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	MI2021	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	2.5(440)	[μF(VAC minimum)]
5 Motor protection	AE37FN10	
6 Start winding resistance	25.40	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	24.60	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	3.90	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.40	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
406	102	119	75	0.39	1.27	5.44	1.37	1.59

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	207	52	61	48	0.32	0.65	4.30	1.08	1.26
-30	(-22)	292	74	86	58	0.34	0.92	5.04	1.27	1.48
-25	(-13)	391	99	115	68	0.37	1.23	5.77	1.45	1.69
-20	(- 4)	508	128	149	78	0.40	1.60	6.52	1.64	1.91
-15	(+ 5)	646	163	189	88	0.43	2.03	7.33	1.85	2.15
-10	(+14)	808	204	237	98	0.46	2.55	8.21	2.07	2.41

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	182	46	53	49	0.32	0.57	3.76	0.95	1.10
-30	(-22)	268	68	79	60	0.35	0.84	4.47	1.13	1.31
-25	(-13)	367	93	108	71	0.38	1.15	5.15	1.30	1.51
-20	(- 4)	483	122	142	83	0.41	1.52	5.82	1.47	1.71
-15	(+ 5)	620	156	182	95	0.45	1.95	6.52	1.64	1.91
-10	(+14)	781	197	229	107	0.49	2.46	7.29	1.84	2.14

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	164	41	48	48	0.32	0.51	3.38	0.85	0.99
-30	(-22)	247	62	72	61	0.35	0.77	4.04	1.02	1.18
-25	(-13)	342	86	100	74	0.39	1.08	4.64	1.17	1.36
-20	(- 4)	455	115	133	87	0.43	1.43	5.21	1.31	1.53
-15	(+ 5)	588	148	172	102	0.48	1.85	5.79	1.46	1.70
-10	(+14)	745	188	218	116	0.52	2.35	6.41	1.61	1.88

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		