

COMPRESSOR DEFINITION

Designation	EG US60HLP
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513701095

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	98 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	-	98 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/5	[hp]
2 Displacement	5.09	[cm ³] (0.311 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	12.800	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	10.39	[kg] (22.91 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	7M4R7MC1/8EA14C1/8EA21C1/8M4R7MC1	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	4TM319NFBYY-53	
6 Start winding resistance	10.68	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	4.49	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	11.60	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	2.04	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	2.43	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
610	154	179	113	1.39	3.47	5.40	1.36	1.58

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	314	79	92	75	0.93	1.78	4.22	1.06	1.24
-30 (-22)	423	107	124	89	1.10	2.40	4.83	1.22	1.42
-25 (-13)	600	151	176	107	1.32	3.41	5.63	1.42	1.65
-20 (- 4)	833	210	244	126	1.54	4.74	6.58	1.66	1.93
-15 (+ 5)	1109	280	325	145	1.77	6.33	7.66	1.93	2.24
-10 (+14)	1417	357	415	161	1.96	8.12	8.83	2.22	2.59

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	249	63	73	66	0.84	1.41	3.68	0.93	1.08
-30 (-22)	358	90	105	83	1.04	2.03	4.32	1.09	1.27
-25 (-13)	533	134	156	105	1.29	3.02	5.07	1.28	1.48
-20 (- 4)	762	192	223	129	1.57	4.33	5.88	1.48	1.72
-15 (+ 5)	1032	260	303	153	1.87	5.89	6.74	1.70	1.97
-10 (+14)	1332	336	390	176	2.15	7.63	7.60	1.92	2.23

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	155	39	45	60	0.77	0.88	2.65	0.67	0.78
-30 (-22)	267	67	78	78	0.97	1.51	3.48	0.88	1.02
-25 (-13)	444	112	130	102	1.25	2.52	4.32	1.09	1.27
-20 (- 4)	673	170	197	130	1.57	3.83	5.16	1.30	1.51
-15 (+ 5)	942	237	276	159	1.93	5.38	5.95	1.50	1.74
-10 (+14)	1239	312	363	187	2.28	7.10	6.67	1.68	1.95

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		