

COMPRESSOR DEFINITION

Designation	NJ 9238E
Nominal Voltage/Frequency	230 V 50 Hz
Engineering Number	143QV01

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-22		
3 Nominal voltage and frequency	230 / 50	[V / Hz]	
4 Application type	Medium-High Back pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	21.7	[kgf/cm ²] (309 psig)	/ °C - °F
9.2 Peak	24.2	[kgf/cm ²] (344 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1 1/2	[hp]
2 Displacement	32.67	[cm ³] (1.994 cu.in)
2.1 Bore [mm]	41.770	
2.2 Stroke [mm]	23.850	
3 Lubricant charge	750	[ml] (25.36 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO46	
4 Weight (with oil charge)	22.2	[kg] (48.94 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	230 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA3H3C-108	
3 Start capacitor	88-108(330)	[µF(VAC minimum)]
4 Run capacitor	25(440)	[µF(VAC minimum)]
5 Motor protection	CST00HK-3031	
6 Start winding resistance	5.40	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.75	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @230V50Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
15278	3850	4477	1856	8.18	94.36	8.23	2.07	2.41

E - PERFORMANCE - CURVES

TEST CONDITIONS: @230V50Hz		ASHRAE46 Fan				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	5757	1451	1687	1016	4.89	30.13	5.65	1.42	1.66
-15	(+ 5)	7325	1846	2147	1119	5.30	38.47	6.55	1.65	1.92
-10	(+14)	9293	2342	2723	1214	5.73	48.99	7.66	1.93	2.24
-5	(+23)	11661	2938	3417	1300	6.15	61.76	8.97	2.26	2.63
0	(+32)	14428	3636	4228	1379	6.59	76.85	10.47	2.64	3.07
+5	(+41)	17594	4434	5156	1449	7.02	94.36	12.15	3.06	3.56
+10	(+50)	21161	5333	6201	1510	7.46	114.35	14.00	3.53	4.10

TEST CONDITIONS: @230V50Hz		ASHRAE46 Fan				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	5274	1329	1545	1054	5.04	29.44	5.02	1.27	1.47
-15	(+ 5)	6730	1696	1972	1181	5.53	37.76	5.71	1.44	1.67
-10	(+14)	8521	2147	2497	1301	6.03	48.01	6.54	1.65	1.92
-5	(+23)	10646	2683	3119	1415	6.52	60.29	7.50	1.89	2.20
0	(+32)	13105	3302	3840	1521	7.00	74.66	8.60	2.17	2.52
+5	(+41)	15899	4007	4659	1621	7.48	91.20	9.81	2.47	2.87
+10	(+50)	19027	4795	5575	1713	7.95	110.00	11.13	2.80	3.26

TEST CONDITIONS: @230V50Hz		ASHRAE46 Fan				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	4778	1204	1400	1093	5.19	28.73	4.36	1.10	1.28
-15	(+ 5)	6111	1540	1791	1245	5.77	36.89	4.91	1.24	1.44
-10	(+14)	7713	1944	2260	1392	6.34	46.76	5.55	1.40	1.63
-5	(+23)	9584	2415	2808	1534	6.89	58.41	6.25	1.58	1.83
0	(+32)	11724	2954	3435	1670	7.43	71.93	7.03	1.77	2.06
+5	(+41)	14133	3562	4141	1800	7.95	87.39	7.85	1.98	2.30
+10	(+50)	16812	4237	4926	1925	8.46	104.87	8.72	2.20	2.56

F - EXTERNAL CHARACTERISTICS

1 Base plate	American Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	12.77 +0.08/+0.00	[mm]	(0.503" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	8 +0.07/+0.00	[mm]	(0.315" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted J		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		