

COMPRESSOR DEFINITION

Designation	EG X80CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513703005

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	187 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	187 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	11.14	[cm ³] (0.680 cu.in)
2.1 Bore [mm]	26.000	
2.2 Stroke [mm]	21.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	10.97	[kg] (24.18 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA17C3/8EA5B3/QPS2-A22MD3/QPS2-A22MD3 091	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(310)	[µF(VAC minimum)]
5 Motor protection	4TM189NFBYY-53	
6 Start winding resistance	22.45	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	18.35	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	5.10	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.85	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - CE - UKCA - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
679	171	199	107	0.49	2.13	6.36	1.60	1.86

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	387	98	113	75	0.36	1.21	5.18	1.30	1.52
-30 (-22)	505	127	148	86	0.40	1.58	5.88	1.48	1.72
-25 (-13)	648	163	190	97	0.45	2.03	6.70	1.69	1.96
-20 (- 4)	824	208	242	108	0.50	2.59	7.62	1.92	2.23
-15 (+ 5)	1040	262	305	120	0.55	3.27	8.63	2.17	2.53
-10 (+14)	1300	328	381	133	0.61	4.10	9.72	2.45	2.85

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	363	91	106	77	0.37	1.14	4.71	1.19	1.38
-30 (-22)	481	121	141	90	0.42	1.51	5.34	1.35	1.57
-25 (-13)	622	157	182	103	0.47	1.95	6.06	1.53	1.78
-20 (- 4)	793	200	232	116	0.53	2.49	6.85	1.73	2.01
-15 (+ 5)	1000	252	293	130	0.59	3.15	7.70	1.94	2.26
-10 (+14)	1249	315	366	145	0.66	3.94	8.61	2.17	2.52

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	332	84	97	77	0.37	1.04	4.30	1.08	1.26
-30 (-22)	449	113	132	91	0.43	1.41	4.89	1.23	1.43
-25 (-13)	586	148	172	106	0.49	1.84	5.54	1.40	1.62
-20 (- 4)	750	189	220	121	0.55	2.36	6.22	1.57	1.82
-15 (+ 5)	947	239	278	137	0.62	2.98	6.94	1.75	2.03
-10 (+14)	1184	298	347	154	0.70	3.74	7.68	1.94	2.25

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EG/F/AMEM Version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		