

COMPRESSOR DEFINITION

Designation	EM X70CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513309516

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	11.14	[cm ³] (0.680 cu.in)
2.1 Bore [mm]	26.000	
2.2 Stroke [mm]	21.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	8.6	[kg] (18.96 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	V230	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	5(300)	[µF(VAC minimum)]
5 Motor protection	T0225/07	
6 Start winding resistance	14.10	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	18.80	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	4.90	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.85	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CE - IRAM - UKCA - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
652	164	191	114	0.55	2.05	5.70	1.44	1.67

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	314	79	92	87	0.48	0.98	3.60	0.91	1.06
-30 (-22)	466	118	137	93	0.44	1.46	5.01	1.26	1.47
-25 (-13)	623	157	182	104	0.47	1.95	5.99	1.51	1.75
-20 (- 4)	795	200	233	119	0.55	2.50	6.70	1.69	1.96
-15 (+ 5)	995	251	292	136	0.66	3.13	7.29	1.84	2.14
-10 (+14)	1236	311	362	155	0.77	3.90	7.93	2.00	2.32

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	268	68	79	86	0.40	0.84	3.14	0.79	0.92
-30 (-22)	428	108	125	94	0.37	1.34	4.53	1.14	1.33
-25 (-13)	589	148	173	107	0.42	1.85	5.48	1.38	1.61
-20 (- 4)	764	193	224	125	0.52	2.40	6.13	1.54	1.80
-15 (+ 5)	966	243	283	145	0.65	3.04	6.65	1.68	1.95
-10 (+14)	1205	304	353	167	0.78	3.80	7.19	1.81	2.11

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	231	58	68	85	0.48	0.72	2.71	0.68	0.80
-30 (-22)	391	99	115	95	0.46	1.23	4.08	1.03	1.19
-25 (-13)	551	139	162	111	0.51	1.73	4.97	1.25	1.46
-20 (- 4)	723	182	212	131	0.62	2.27	5.56	1.40	1.63
-15 (+ 5)	919	232	269	154	0.75	2.89	5.99	1.51	1.75
-10 (+14)	1151	290	337	179	0.88	3.63	6.42	1.62	1.88

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted parallel BP+24°to Back		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 43° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		