

COMPRESSOR DEFINITION

| | |
|---------------------------|--------------------|
| Designation | EG AS70HLR |
| Nominal Voltage/Frequency | 220-240 V 50-60 Hz |
| Engineering Number | 513701005 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|------------------------------------|-----------------------------------|-----------------------------------|--------------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-134a | | |
| 3 Nominal voltage and frequency | 220-240 / 50-60 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSIR-CSIR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | Operating voltage range | | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | 198 to 255 V | 198 to 255 V |
| 8.2 LBP (43°C Ambient temperature) | Static | 198 to 255 V | 198 to 255 V |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing temperature | | | |
| 9.1 Operating | 14.2 | [kgf/cm ²] (202 psig) | / °C - °F |
| 9.2 Peak | 15.9 | [kgf/cm ²] (226 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|---------------|--|
| 1 Commercial designation | 1/5+ | [hp] |
| 2 Displacement | 5.56 | [cm ³] (0.339 cu.in) |
| 2.1 Bore [mm] | 22.500 | |
| 2.2 Stroke [mm] | 14.000 | |
| 3 Lubricant charge | 280 | [ml] (9.47 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ESTER / ISO10 | |
| 4 Weight (with oil charge) | 10.39 | [kg] (22.91 lb.) |
| 5 Nitrogen charge | 0.2 to 0.3 | [kgf/cm ²] (2.84 to 4.27 psig) |

C - ELETRICAL DATA

| | | |
|--|---------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50-60 Hz 1 ~ (Single phase) | |
| 2 Starting device type | Current Relay | |
| 2.1 Starting device | 213516256/213516493 | |
| 3 Start capacitor | 88-108(180) | [µF(VAC minimum)] |
| 4 Run capacitor | - | [µF(VAC minimum)] |
| 5 Motor protection | 4TM739KFBYY-53 | |
| 6 Start winding resistance | 30.50 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 12.35 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (50/60 Hz) | 14.40/13.40 | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50/60 Hz) | 1.55/1.40 | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (50/60 Hz) | 1.85/1.65 | [A] - Measured according to UL 984 |
| 11 Approval boards certification | CE - IRAM - TUV - UKCA - VDE | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|-------------------------------|----------|-----|--------------------------------|----------------------------------|--|---------------------------|--|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 560 | 141 | 164 | 111 | 0.96 | 3.18 | 5.03 | 1.27 | 1.47 |

| | | | | | | | | |
|-------------------------------|----------|-----|--------------------------------|----------------------------------|--|---------------------------|--|-------|
| TEST CONDITIONS: @220V60Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 695 | 175 | 204 | 129 | 0.88 | 3.95 | 5.40 | 1.36 | 1.58 |

E - PERFORMANCE - CURVES

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 45°C (+113°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 270 | 68 | 79 | 72 | 0.62 | 1.53 | 3.76 | 0.95 | 1.10 |
| -30 (-22) | 400 | 101 | 117 | 88 | 0.75 | 2.27 | 4.50 | 1.13 | 1.32 |
| -25 (-13) | 563 | 142 | 165 | 106 | 0.90 | 3.20 | 5.28 | 1.33 | 1.55 |
| -20 (- 4) | 756 | 190 | 221 | 124 | 1.06 | 4.30 | 6.11 | 1.54 | 1.79 |
| -15 (+ 5) | 972 | 245 | 285 | 140 | 1.21 | 5.55 | 6.98 | 1.76 | 2.05 |
| -10 (+14) | 1209 | 305 | 354 | 155 | 1.34 | 6.93 | 7.88 | 1.99 | 2.31 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 55°C (+131°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 230 | 58 | 67 | 64 | 0.56 | 1.30 | 3.63 | 0.91 | 1.06 |
| -30 (-22) | 343 | 86 | 101 | 82 | 0.72 | 1.94 | 4.17 | 1.05 | 1.22 |
| -25 (-13) | 496 | 125 | 145 | 104 | 0.89 | 2.81 | 4.77 | 1.20 | 1.40 |
| -20 (- 4) | 683 | 172 | 200 | 126 | 1.08 | 3.89 | 5.40 | 1.36 | 1.58 |
| -15 (+ 5) | 901 | 227 | 264 | 148 | 1.28 | 5.14 | 6.07 | 1.53 | 1.78 |
| -10 (+14) | 1146 | 289 | 336 | 169 | 1.47 | 6.56 | 6.78 | 1.71 | 1.99 |

E - PERFORMANCE - CURVES

| TEST CONDITIONS: @220V50Hz | | ASHRAE32 Static | | | (Condensing temperature 65°C (+149°F)) | | | | | |
|-------------------------------|----------------------------|--------------------|----------|-----------------------------|--|-------------------------|---------------------------|----------|-----------|-------|
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| | °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 181 | 46 | 53 | 57 | 0.51 | 1.02 | 3.16 | 0.80 | 0.93 | |
| -30 (-22) | 274 | 69 | 80 | 77 | 0.67 | 1.55 | 3.63 | 0.91 | 1.06 | |
| -25 (-13) | 412 | 104 | 121 | 100 | 0.86 | 2.34 | 4.14 | 1.04 | 1.21 | |
| -20 (- 4) | 592 | 149 | 173 | 126 | 1.08 | 3.37 | 4.69 | 1.18 | 1.37 | |
| -15 (+ 5) | 808 | 204 | 237 | 152 | 1.32 | 4.62 | 5.28 | 1.33 | 1.55 | |
| -10 (+14) | 1058 | 266 | 310 | 179 | 1.56 | 6.06 | 5.91 | 1.49 | 1.73 | |

| TEST CONDITIONS: @220V60Hz | | ASHRAE32 Static | | | (Condensing temperature 45°C (+113°F)) | | | | | |
|-------------------------------|----------------------------|--------------------|----------|-----------------------------|--|-------------------------|---------------------------|----------|-----------|-------|
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| | °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 335 | 85 | 98 | 83 | 0.57 | 1.90 | 4.04 | 1.02 | 1.18 | |
| -30 (-22) | 497 | 125 | 146 | 102 | 0.69 | 2.82 | 4.83 | 1.22 | 1.42 | |
| -25 (-13) | 700 | 176 | 205 | 123 | 0.83 | 3.97 | 5.67 | 1.43 | 1.66 | |
| -20 (- 4) | 938 | 236 | 275 | 143 | 0.97 | 5.34 | 6.56 | 1.65 | 1.92 | |
| -15 (+ 5) | 1207 | 304 | 354 | 162 | 1.10 | 6.89 | 7.49 | 1.89 | 2.19 | |
| -10 (+14) | 1501 | 378 | 440 | 179 | 1.23 | 8.60 | 8.46 | 2.13 | 2.48 | |

| TEST CONDITIONS: @220V60Hz | | ASHRAE32 Static | | | (Condensing temperature 55°C (+131°F)) | | | | | |
|-------------------------------|----------------------------|--------------------|----------|-----------------------------|--|-------------------------|---------------------------|----------|-----------|-------|
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| | °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 286 | 72 | 84 | 73 | 0.51 | 1.62 | 3.90 | 0.98 | 1.14 | |
| -30 (-22) | 426 | 107 | 125 | 95 | 0.65 | 2.42 | 4.49 | 1.13 | 1.31 | |
| -25 (-13) | 616 | 155 | 180 | 120 | 0.81 | 3.50 | 5.12 | 1.29 | 1.50 | |
| -20 (- 4) | 848 | 214 | 249 | 146 | 0.99 | 4.83 | 5.80 | 1.46 | 1.70 | |
| -15 (+ 5) | 1119 | 282 | 328 | 171 | 1.17 | 6.39 | 6.52 | 1.64 | 1.91 | |
| -10 (+14) | 1422 | 358 | 417 | 196 | 1.34 | 8.15 | 7.28 | 1.83 | 2.13 | |

| TEST CONDITIONS: @220V60Hz | | ASHRAE32 Static | | | (Condensing temperature 65°C (+149°F)) | | | | | |
|-------------------------------|----------------------------|--------------------|----------|-----------------------------|--|-------------------------|---------------------------|----------|-----------|-------|
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| | °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 224 | 56 | 66 | 66 | 0.47 | 1.27 | 3.39 | 0.85 | 0.99 | |
| -30 (-22) | 340 | 86 | 100 | 89 | 0.61 | 1.93 | 3.89 | 0.98 | 1.14 | |
| -25 (-13) | 512 | 129 | 150 | 116 | 0.79 | 2.91 | 4.44 | 1.12 | 1.30 | |
| -20 (- 4) | 735 | 185 | 215 | 145 | 0.99 | 4.18 | 5.04 | 1.27 | 1.48 | |
| -15 (+ 5) | 1004 | 253 | 294 | 176 | 1.21 | 5.73 | 5.67 | 1.43 | 1.66 | |
| -10 (+14) | 1313 | 331 | 385 | 206 | 1.43 | 7.52 | 6.34 | 1.60 | 1.86 | |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|---------------------------------------|------|--------------------------|
| 1 Base plate | European Standard EG/F/AMEM Version 2 | | |
| 2 Tray holder | No | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 8.2 +0.12/-0.08 | [mm] | (0.323" +0.005"/-0.003") |
| 3.1.1 Material | Copper plated steel | | |
| 3.1.2 Shape | Slanted | | |
| 3.2 DISCHARGE | 5 +0.18/-0.06 | [mm] | (0.197" +0.007"/-0.002") |
| 3.2.1 Material | Copper plated steel | | |
| 3.2.2 Shape | Slanted | | |
| 3.3 PROCESS | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.3.1 Material | Copper plated steel | | |
| 3.3.2 Shape | Slanted | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |