

### COMPRESSOR DEFINITION

Designation	EG US80HLP
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513701038

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	98 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	-	98 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm <sup>2</sup> ] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm <sup>2</sup> ] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	6.36	[cm <sup>3</sup> ] (0.388 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	16.000	
3 Lubricant charge	230	[ml] (7.78 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	10.2	[kg] (22.49 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA14C1/8EA21C1/QPS2-A4R7MG1/QPS2-A4R7MG1 090	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	4TM445KFBYY-53	
6 Start winding resistance	7.80	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	3.30	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	16.40	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	2.85	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	3.35	[A] - Measured according to UL 984
11 Approval boards certification	CE - UKCA - UL - VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
806	203	236	147	1.90	4.58	5.49	1.38	1.61

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	401	101	117	97	1.25	2.27	4.12	1.04	1.21
-30 (-22)	602	152	176	119	1.52	3.41	5.03	1.27	1.47
-25 (-13)	823	207	241	140	1.79	4.67	5.87	1.48	1.72
-20 (- 4)	1074	271	315	161	2.05	6.11	6.68	1.68	1.96
-15 (+ 5)	1366	344	400	182	2.30	7.80	7.55	1.90	2.21
-10 (+14)	1710	431	501	201	2.55	9.80	8.51	2.14	2.49

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	324	82	95	87	1.13	1.83	3.72	0.94	1.09
-30 (-22)	517	130	151	112	1.46	2.93	4.55	1.15	1.33
-25 (-13)	734	185	215	139	1.79	4.17	5.28	1.33	1.55
-20 (- 4)	988	249	289	165	2.12	5.62	5.97	1.50	1.75
-15 (+ 5)	1287	324	377	193	2.46	7.35	6.67	1.68	1.96
-10 (+14)	1644	414	482	220	2.81	9.42	7.46	1.88	2.19

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	248	63	73	80	1.04	1.41	3.13	0.79	0.92
-30 (-22)	426	107	125	107	1.39	2.41	3.96	1.00	1.16
-25 (-13)	633	159	185	136	1.75	3.59	4.65	1.17	1.36
-20 (- 4)	881	222	258	167	2.13	5.01	5.29	1.33	1.55
-15 (+ 5)	1181	298	346	199	2.53	6.74	5.92	1.49	1.73
-10 (+14)	1542	389	452	232	2.94	8.84	6.61	1.67	1.94

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.2 +0.12/-0.08	[mm]	(0.323" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		