

COMPRESSOR DEFINITION

| | |
|---------------------------|-----------------|
| Designation | EM X26CLC |
| Nominal Voltage/Frequency | 220-240 V 50 Hz |
| Engineering Number | 513309524 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|--|-----------------------------------|-----------------------------------|-----------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-600a | | |
| 3 Nominal voltage and frequency | 220-240 / 50 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSCR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | Operating voltage range | | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | 187 to 255 V | - |
| 8.2 LBP (43°C Ambient temperature) | Static | 187 to 255 V | - |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing pressures/temperature | | | |
| 9.1 Operating (gauge) | 7.7 | [kgf/cm ²] (109 psig) | / °C - °F |
| 9.2 Peak (gauge) | 9.8 | [kgf/cm ²] (139 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|----------------|----------------------------------|
| 1 Commercial designation | 1/10 | [hp] |
| 2 Displacement | 5.19 | [cm ³] (0.317 cu.in) |
| 2.1 Bore [mm] | 21.000 | |
| 2.2 Stroke [mm] | 15.000 | |
| 3 Lubricant charge | 180 | [ml] (6.09 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ALQUILB / ISO5 | |
| 4 Weight (with oil charge) | 7.88 | [kg] (17.37 lb.) |
| 5 Nitrogen charge | - | [kgf/cm ²] |

C - ELETRICAL DATA

| | | |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50 Hz 1 ~ (Single phase) | |
| 2 Starting device type | TSD | |
| 2.1 Starting device | TSD-220V0.6 | |
| 3 Start capacitor | - | [µF(VAC minimum)] |
| 4 Run capacitor | 2.5(380) | [µF(VAC minimum)] |
| 5 Motor protection | 4TM 110NFBYY-73 | |
| 6 Start winding resistance | 28.90 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 42.70 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (50 Hz) | 2.40 | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50 Hz) | 0.40 | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (50 Hz) | - | [A] - Measured according to UL 984 |
| 11 Approval boards certification | IRAM - VDE | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|-------------------------------|----------|-----|-----------------------------|-------------------------------|--|---------------------------|--|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 285 | 72 | 84 | 50 | 0.23 | 0.89 | 5.75 | 1.45 | 1.68 |

E - PERFORMANCE - CURVES

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|-----------------------------|--|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 45°C (+113°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 140 | 35 | 41 | 33 | 0.16 | 0.44 | 4.23 | 1.07 | 1.24 |
| -30 (-22) | 211 | 53 | 62 | 39 | 0.19 | 0.66 | 5.34 | 1.34 | 1.56 |
| -25 (-13) | 280 | 71 | 82 | 45 | 0.21 | 0.88 | 6.22 | 1.57 | 1.82 |
| -20 (- 4) | 357 | 90 | 105 | 51 | 0.24 | 1.12 | 7.04 | 1.78 | 2.06 |
| -15 (+ 5) | 450 | 113 | 132 | 56 | 0.26 | 1.42 | 7.96 | 2.01 | 2.33 |
| -10 (+14) | 568 | 143 | 167 | 62 | 0.28 | 1.79 | 9.13 | 2.30 | 2.68 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|-----------------------------|--|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 55°C (+131°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 107 | 27 | 31 | 33 | 0.15 | 0.33 | 3.28 | 0.83 | 0.96 |
| -30 (-22) | 184 | 46 | 54 | 40 | 0.19 | 0.58 | 4.51 | 1.14 | 1.32 |
| -25 (-13) | 258 | 65 | 76 | 47 | 0.22 | 0.81 | 5.44 | 1.37 | 1.59 |
| -20 (- 4) | 337 | 85 | 99 | 55 | 0.25 | 1.06 | 6.21 | 1.56 | 1.82 |
| -15 (+ 5) | 431 | 109 | 126 | 62 | 0.28 | 1.36 | 6.99 | 1.76 | 2.05 |
| -10 (+14) | 548 | 138 | 161 | 69 | 0.31 | 1.73 | 7.92 | 2.00 | 2.32 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|-----------------------------|--|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 65°C (+149°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 73 | 18 | 21 | 30 | 0.14 | 0.23 | 2.45 | 0.62 | 0.72 |
| -30 (-22) | 154 | 39 | 45 | 39 | 0.18 | 0.48 | 3.81 | 0.96 | 1.12 |
| -25 (-13) | 229 | 58 | 67 | 48 | 0.22 | 0.72 | 4.77 | 1.20 | 1.40 |
| -20 (- 4) | 307 | 77 | 90 | 57 | 0.26 | 0.97 | 5.48 | 1.38 | 1.61 |
| -15 (+ 5) | 398 | 100 | 117 | 66 | 0.30 | 1.25 | 6.11 | 1.54 | 1.79 |
| -10 (+14) | 510 | 129 | 149 | 75 | 0.34 | 1.61 | 6.80 | 1.71 | 1.99 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|------------------------------|------|--------------------------|
| 1 Base plate | European Standard EUEM | | |
| 2 Tray holder | No | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Slanted 42° up + 45° to Back | | |
| 3.2 DISCHARGE | 5.1 +0.10/+0.00 | [mm] | (0.201" +0.004"/+0.000") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Slanted 42° up + 24° to Back | | |
| 3.3 PROCESS | 6 +0.08/-0.08 | [mm] | (0.236" +0.003"/-0.003") |
| 3.3.1 Material | Copper(OD) | | |
| 3.3.2 Shape | Slanted 43° up + 45° to Back | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |