

COMPRESSOR DEFINITION

Designation	EM Y45HSC
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513308583

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	85 to 110 V	103 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	85 to 110 V	103 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/8	[hp]
2 Displacement	3.77	[cm ³] (0.230 cu.in)
2.1 Bore [mm]	19.000	
2.2 Stroke [mm]	13.300	
3 Lubricant charge	160	[ml] (5.41 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	7.85	[kg] (17.31 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA14C3/8EA1B3/8EA21C3/8EA3B3/8EA4B3/QPS2-A4R7MD3	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	12(180)	[µF(VAC minimum)]
5 Motor protection	4TM283NFBYY-53	
6 Start winding resistance	5.40	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	6.15	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	8.40/7.40	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	1.20	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CE - UKCA - UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
455	115	133	89	0.80	2.59	5.14	1.30	1.51

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	237	60	69	63	0.60	1.34	3.79	0.95	1.11
-30 (-22)	348	88	102	72	0.66	1.97	4.77	1.20	1.40
-25 (-13)	459	116	134	82	0.74	2.60	5.57	1.40	1.63
-20 (- 4)	581	146	170	92	0.83	3.31	6.31	1.59	1.85
-15 (+ 5)	728	183	213	103	0.92	4.15	7.09	1.79	2.08
-10 (+14)	912	230	267	113	1.02	5.23	8.04	2.02	2.35

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	208	53	61	62	0.59	1.18	3.35	0.84	0.98
-30 (-22)	311	78	91	73	0.68	1.76	4.21	1.06	1.23
-25 (-13)	415	105	122	85	0.77	2.36	4.89	1.23	1.43
-20 (- 4)	534	135	156	97	0.88	3.04	5.51	1.39	1.61
-15 (+ 5)	680	171	199	110	0.99	3.88	6.17	1.56	1.81
-10 (+14)	866	218	254	123	1.11	4.96	6.99	1.76	2.05

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	165	42	48	59	0.56	0.93	2.77	0.70	0.81
-30 (-22)	255	64	75	72	0.66	1.45	3.53	0.89	1.03
-25 (-13)	350	88	103	86	0.78	1.99	4.11	1.04	1.20
-20 (- 4)	461	116	135	101	0.91	2.62	4.63	1.17	1.36
-15 (+ 5)	603	152	177	116	1.04	3.44	5.19	1.31	1.52
-10 (+14)	786	198	230	132	1.18	4.51	5.90	1.49	1.73

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		