

### COMPRESSOR DEFINITION

Designation	EG ZS60HLP
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513701149

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	98 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	-	98 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm <sup>2</sup> ] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm <sup>2</sup> ] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/5	[hp]
2 Displacement	5.09	[cm <sup>3</sup> ] (0.311 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	12.800	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	10.75	[kg] (23.70 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA14C3/8EA21C3/QPS2-A4R7MD3/QPS2-A4R7MD3 094	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	12(180)/15(200)/20(200)	[µF(VAC minimum)]
5 Motor protection	4TM427KFBYY-53	
6 Start winding resistance	6.00	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	5.15	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	10.40	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	1.56	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	1.90	[A] - Measured according to UL 984
11 Approval boards certification	CE - UKCA - UL	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
610	154	179	104	0.91	3.47	5.87	1.48	1.72

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	314	79	92	69	0.61	1.78	4.59	1.16	1.34
-30 (-22)	423	107	124	82	0.72	2.40	5.25	1.32	1.54
-25 (-13)	600	151	176	98	0.86	3.41	6.12	1.54	1.79
-20 (- 4)	833	210	244	116	1.01	4.74	7.16	1.80	2.10
-15 (+ 5)	1109	280	325	133	1.16	6.33	8.33	2.10	2.44
-10 (+14)	1417	357	415	148	1.28	8.12	9.60	2.42	2.81

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	249	63	73	61	0.55	1.41	4.01	1.01	1.17
-30 (-22)	358	90	105	77	0.68	2.03	4.70	1.19	1.38
-25 (-13)	533	134	156	96	0.84	3.02	5.51	1.39	1.62
-20 (- 4)	762	192	223	119	1.03	4.33	6.40	1.61	1.88
-15 (+ 5)	1032	260	303	141	1.22	5.89	7.33	1.85	2.15
-10 (+14)	1332	336	390	162	1.40	7.63	8.27	2.08	2.42

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	155	39	45	55	0.50	0.88	2.88	0.73	0.84
-30 (-22)	267	67	78	72	0.64	1.51	3.78	0.95	1.11
-25 (-13)	444	112	130	94	0.82	2.52	4.70	1.18	1.38
-20 (- 4)	673	170	197	119	1.04	3.83	5.61	1.41	1.64
-15 (+ 5)	942	237	276	146	1.26	5.38	6.47	1.63	1.90
-10 (+14)	1239	312	363	172	1.50	7.10	7.26	1.83	2.13

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		