

### COMPRESSOR DEFINITION

Designation	NB Y1121Y
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	816CA42

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	7.7	[kgf/cm <sup>2</sup> ] (109 psig)	/ °C - °F
9.2 Peak (gauge)	9.8	[kgf/cm <sup>2</sup> ] (139 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	15.71	[cm <sup>3</sup> ] (0.959 cu.in)
2.1 Bore [mm]	30.157	
2.2 Stroke [mm]	22.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	10.6	[kg] (23.37 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	V230	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(440)	[µF(VAC minimum)]
5 Motor protection	T0503/07	
6 Start winding resistance	15.60	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	12.80	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			CECOMAFLBP Static		Evaporating temperature (Condensing temperature		-25°C (-13°F) 55°C (131°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
663	167	194	145	0.71	2.53	4.57	1.15	1.34

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		CECOMAF Static			(Condensing temperature 35°C (+95°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	503	127	147	96	0.50	1.61	5.22	1.32	1.53
-30	(-22)	653	165	191	112	0.56	2.09	5.85	1.47	1.71
-25	(-13)	855	216	251	128	0.63	2.75	6.68	1.68	1.96
-20	(- 4)	1108	279	325	145	0.70	3.56	7.66	1.93	2.24
-15	(+ 5)	1411	356	413	162	0.77	4.54	8.74	2.20	2.56
-10	(+14)	1763	444	517	179	0.85	5.69	9.88	2.49	2.90

TEST CONDITIONS: @220V50Hz		CECOMAF Static			(Condensing temperature 45°C (+113°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	454	114	133	102	0.51	1.58	4.48	1.13	1.31
-30	(-22)	573	144	168	118	0.58	1.99	4.89	1.23	1.43
-25	(-13)	743	187	218	135	0.66	2.59	5.48	1.38	1.61
-20	(- 4)	964	243	282	154	0.74	3.36	6.22	1.57	1.82
-15	(+ 5)	1234	311	362	174	0.83	4.31	7.06	1.78	2.07
-10	(+14)	1553	391	455	195	0.92	5.44	7.95	2.00	2.33

TEST CONDITIONS: @220V50Hz		CECOMAF Static			(Condensing temperature 55°C (+131°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	427	108	125	108	0.53	1.62	3.93	0.99	1.15
-30	(-22)	516	130	151	125	0.61	1.96	4.14	1.04	1.21
-25	(-13)	654	165	192	144	0.70	2.50	4.54	1.14	1.33
-20	(- 4)	842	212	247	166	0.79	3.22	5.08	1.28	1.49
-15	(+ 5)	1079	272	316	189	0.90	4.13	5.70	1.44	1.67
-10	(+14)	1365	344	400	215	1.02	5.24	6.36	1.60	1.86

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted parallel to Base Plate		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		