

COMPRESSOR DEFINITION

| | |
|---------------------------|------------------------|
| Designation | NB U1118Y. |
| Nominal Voltage/Frequency | 220-240 V 50 Hz |
| Engineering Number | 815DA61 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|------------------------------------|-----------------------------------|-----------------------------------|-----------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-600a | | |
| 3 Nominal voltage and frequency | 220-240 / 50 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSCR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | Operating voltage range | | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | 198 to 254 V | - |
| 8.2 LBP (43°C Ambient temperature) | Static | 198 to 254 V | - |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing temperature | | | |
| 9.1 Operating | 6.9 | [kgf/cm ²] (98 psig) | / °C - °F |
| 9.2 Peak | 7.8 | [kgf/cm ²] (111 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|----------------|----------------------------------|
| 1 Commercial designation | | [hp] |
| 2 Displacement | 14.28 | [cm ³] (0.871 cu.in) |
| 2.1 Bore [mm] | 30.157 | |
| 2.2 Stroke [mm] | 20.000 | |
| 3 Lubricant charge | 280 | [ml] (9.47 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | MINERAL / ISO7 | |
| 4 Weight (with oil charge) | 10.73 | [kg] (23.66 lb.) |
| 5 Nitrogen charge | - | [kgf/cm ²] |

C - ELETRICAL DATA

| | | |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50 Hz 1 ~ (Single phase) | |
| 2 Starting device type | PTC | |
| 2.1 Starting device | V230 | |
| 3 Start capacitor | - | [µF(VAC minimum)] |
| 4 Run capacitor | 4(450) | [µF(VAC minimum)] |
| 5 Motor protection | T0062/07 | |
| 6 Start winding resistance | 22.90 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 15.68 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (50 Hz) | - | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50 Hz) | - | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (50 Hz) | - | [A] - Measured according to UL 984 |
| 11 Approval boards certification | VDE | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|-------------------------------|----------|-----|--------------------------------|----------------------------------|--|---------------------------|--|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 804 | 203 | 236 | 142 | 0.66 | 2.52 | 5.66 | 1.43 | 1.66 |

E - PERFORMANCE - CURVES

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 35°C (+95°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 507 | 128 | 149 | 92 | 0.46 | 1.59 | 5.53 | 1.39 | 1.62 |
| -30 (-22) | 625 | 158 | 183 | 105 | 0.51 | 1.96 | 6.02 | 1.52 | 1.77 |
| -25 (-13) | 790 | 199 | 232 | 118 | 0.56 | 2.48 | 6.73 | 1.70 | 1.97 |
| -20 (- 4) | 1009 | 254 | 296 | 132 | 0.62 | 3.17 | 7.63 | 1.92 | 2.24 |
| -15 (+ 5) | 1288 | 325 | 377 | 147 | 0.69 | 4.05 | 8.70 | 2.19 | 2.55 |
| -10 (+14) | 1634 | 412 | 479 | 164 | 0.76 | 5.15 | 9.93 | 2.50 | 2.91 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|---|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 45°C (+113°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 487 | 123 | 143 | 97 | 0.47 | 1.52 | 5.01 | 1.26 | 1.47 |
| -30 (-22) | 607 | 153 | 178 | 111 | 0.53 | 1.90 | 5.47 | 1.38 | 1.60 |
| -25 (-13) | 768 | 194 | 225 | 127 | 0.60 | 2.41 | 6.08 | 1.53 | 1.78 |
| -20 (- 4) | 977 | 246 | 286 | 143 | 0.66 | 3.07 | 6.84 | 1.72 | 2.00 |
| -15 (+ 5) | 1239 | 312 | 363 | 161 | 0.74 | 3.90 | 7.71 | 1.94 | 2.26 |
| -10 (+14) | 1563 | 394 | 458 | 180 | 0.83 | 4.93 | 8.68 | 2.19 | 2.54 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|---|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 55°C (+131°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 444 | 112 | 130 | 100 | 0.48 | 1.39 | 4.44 | 1.12 | 1.30 |
| -30 (-22) | 573 | 144 | 168 | 116 | 0.55 | 1.80 | 4.91 | 1.24 | 1.44 |
| -25 (-13) | 736 | 186 | 216 | 134 | 0.63 | 2.31 | 5.48 | 1.38 | 1.61 |
| -20 (- 4) | 941 | 237 | 276 | 153 | 0.71 | 2.96 | 6.14 | 1.55 | 1.80 |
| -15 (+ 5) | 1194 | 301 | 350 | 174 | 0.80 | 3.76 | 6.86 | 1.73 | 2.01 |
| -10 (+14) | 1502 | 379 | 440 | 197 | 0.90 | 4.74 | 7.63 | 1.92 | 2.24 |

E - PERFORMANCE - CURVES

| TEST CONDITIONS: @220V50Hz | | ASHRAE32 Static | | | (Condensing temperature 65°C (+149°F)) | | | | | |
|-------------------------------|-------|----------------------------|----------|-----|---|-------------------------------|-------------------------|---------------------------|-----------|-------|
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 380 | 96 | 111 | 100 | 0.48 | 1.19 | 3.84 | 0.97 | 1.12 |
| -30 | (-22) | 524 | 132 | 154 | 119 | 0.56 | 1.64 | 4.36 | 1.10 | 1.28 |
| -25 | (-13) | 696 | 175 | 204 | 140 | 0.65 | 2.19 | 4.93 | 1.24 | 1.45 |
| -20 | (- 4) | 904 | 228 | 265 | 163 | 0.75 | 2.84 | 5.54 | 1.40 | 1.62 |
| -15 | (+ 5) | 1154 | 291 | 338 | 188 | 0.86 | 3.63 | 6.17 | 1.55 | 1.81 |
| -10 | (+14) | 1452 | 366 | 426 | 215 | 0.98 | 4.58 | 6.79 | 1.71 | 1.99 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|--------------------------------|------|--------------------------|
| 1 Base plate | Universal | | |
| 2 Tray holder | Yes | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Slanted 42° | | |
| 3.2 DISCHARGE | 5.1 +0.10/+0.00 | [mm] | (0.201" +0.004"/+0.000") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Slanted parallel to Base Plate | | |
| 3.3 PROCESS | 6 +0.08/-0.08 | [mm] | (0.236" +0.003"/-0.003") |
| 3.3.1 Material | Copper(OD) | | |
| 3.3.2 Shape | Slanted 42° | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |