

COMPRESSOR DEFINITION

Designation	F FU130UAX
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513200876

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	Low-Medium Back Pressure		
4.1 Evaporating temperature range	-35°C to -5°C	(-31°F to 23°F)	
5 Motor type	CSIR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Fan	-	98 to 140 V
8.2 LBP (43°C Ambient temperature)	Fan	-	98 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm ²] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/3+	[hp]
2 Displacement	6.76	[cm ³] (0.413 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	17.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO32	
4 Weight (with oil charge)	10	[kg] (22.05 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	213516051	
3 Start capacitor	378-454(150)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	MST 26AFZ-5590	
6 Start winding resistance	3.75	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.10	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	41.50	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	8.50	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	9.50	[A] - Measured according to UL 984
11 Approval boards certification	CE - TUV - UKCA - UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1360	343	399	264	4.25	4.05	5.15	1.30	1.51

E - PERFORMANCE - CURVES

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.2 +0.12/-0.08	[mm]	(0.323" +0.005"/-0.003")
3.1.1 Material	Copper plated steel		
3.1.2 Shape	Slanted		
3.2 DISCHARGE	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.2.1 Material	Copper plated steel		
3.2.2 Shape	Slanted		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper plated steel		
3.3.2 Shape	Slanted		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		