

### COMPRESSOR DEFINITION

Designation	EG X90HLC
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513703018

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	98 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	-	98 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm <sup>2</sup> ] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/4+	[hp]
2 Displacement	7.15	[cm <sup>3</sup> ] (0.436 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	18.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO7	
4 Weight (with oil charge)	11.08	[kg] (24.43 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	TSD- 115V	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	15(180)	[µF(VAC minimum)]
5 Motor protection	4TM437NFBYY-53	
6 Start winding resistance	6.05	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	2.95	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	15.10	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	2.40	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - UL	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
950	239	278	151	1.37	5.40	6.27	1.58	1.84

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	499	126	146	100	0.93	2.82	4.96	1.25	1.45
-30 (-22)	704	177	206	119	1.09	3.99	5.88	1.48	1.72
-25 (-13)	934	235	274	140	1.27	5.30	6.70	1.69	1.96
-20 (- 4)	1205	304	353	161	1.45	6.86	7.52	1.90	2.20
-15 (+ 5)	1535	387	450	182	1.64	8.77	8.43	2.12	2.47
-10 (+14)	1942	489	569	203	1.81	11.13	9.54	2.40	2.79

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	412	104	121	96	0.90	2.33	4.32	1.09	1.27
-30 (-22)	626	158	183	119	1.09	3.55	5.24	1.32	1.53
-25 (-13)	859	217	252	143	1.29	4.88	5.99	1.51	1.76
-20 (- 4)	1130	285	331	169	1.51	6.43	6.69	1.69	1.96
-15 (+ 5)	1454	366	426	196	1.74	8.30	7.42	1.87	2.17
-10 (+14)	1851	466	542	222	1.97	10.60	8.29	2.09	2.43

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	316	80	92	85	0.81	1.78	3.70	0.93	1.08
-30 (-22)	533	134	156	113	1.03	3.02	4.63	1.17	1.36
-25 (-13)	765	193	224	142	1.28	4.34	5.36	1.35	1.57
-20 (- 4)	1029	259	302	173	1.55	5.86	5.96	1.50	1.75
-15 (+ 5)	1343	339	394	206	1.83	7.67	6.55	1.65	1.92
-10 (+14)	1724	435	505	239	2.12	9.88	7.21	1.82	2.11

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		